

INDUSTRIAL COMPONENT DATA

IZMX-UVR60DC 124099 EATON ELECTRIC Undervoltage release 60 VDC

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX-UVR60DC



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX-UVR60DC
Catalog number	124099
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-BA1967008C
Generated	2026-08-01

Product Overview

Undervoltage release 60 VDC

IZMX-UVR60DC

Suitable for remote switching off, can be combined only with an undervoltage release

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX undervoltage release Catalog Number 124099 Model Code IZMX-UVR60DC
EAN 4015081217045 Product Length/Depth 150 mm Product Height 100 mm Product Width 100 mm Product Weight 0.091 kg
Compliances CE Marked

RoHS conform Delivery program

Type Accessory Accessory/spare part type Remote switching Technical data - electrical

Voltage type DC Control voltage operating range 60 V DC

0.85 - 1.1 x Us Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 50 Hz - max 0 V
Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V
Rated control supply voltage (Us) at DC - min 60 V Rated control supply voltage (Us) at DC - max 60 V
Current rating - max 0.07 A (maximum holding current) Rated operational current 0.07 A (maximum holding current) Power consumption 5 VA/W
AC/DC Pick-up power consumption at 35 ms - max 890 VA/W Circuit breaker total switching time 37 ms (Us = 100%)

Technical data - mechanical

Number of actuation per minute - max 3 Number of contacts (change-over contacts) 0 Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 0 Design verification as per IEC/EN 61439 - technical data
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Additional information
Special features Suitable for Off-load switch
Power circuit breaker Used with INX16..., INX40....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX-UVR60DC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.