

INDUSTRIAL COMPONENT DATA

NZM2/3-XU600AC 259505 Y7-259505 EATON ELECTRIC

Undervoltage release, 600VAC

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2/3-XU600AC



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2/3-XU600AC
Catalog number	Y7-259505
Category	Under voltage coil
Minimum order	1 Pcs
Document ID	EO-E2791DCA18
Generated	2026-08-04

Product Overview

Undervoltage release, 600VAC

NZM2/3-XU600AC

Eaton Moeller series NZM - Molded Case Circuit Breaker. Undervoltage release, 600VAC, 2/3

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35-70% US. For use with Emergency-Stop devices in conjunction with emergency-stop button. when the undervoltage release is de-energized, accidental contact with the main contacts of the switch during attempts to switch on is safely prevented . Undervoltage releases cannot be installed simultaneously with NZM..-XHIV.. early-make auxiliary contact or NZM..-XA.. shunt release. Can be used for: NZM2(-4), N(N/O)2(-4), NZM3(-4), N(N/O)3(-4)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers NZM

Additional Product Information

General specifications

Product Name Eaton Moeller series NZM release Catalog Number 259505 Model Code NZM2/3-XU600AC EAN 4015082595050 Product Length/Depth 42 mm Product Height 90 mm Product Width 30 mm Product Weight 0.064 kg Compliances UL/CSA

IEC

RoHS conform Certifications CSA (Class No. 1437-01)

CSA (File No. 22086)

UL (File No. E140305)

IEC60947

UL (Category Control Number DIHS)

CE marking

CSA-C22.2 No. 5-09

CSA certified

UL489

UL listed Product specifications

Type Accessory Undervoltage release Special features Non-delayed disconnection of NZM circuit-breaker or N switch-disconnector when the control voltage sinks below 35 - 70% US. For use with emergency-stop devices in connection with an emergency-stop button. When the under-voltage trip is switched off, accidental contact with the circuit breaker's primary contacts is prevented when switched on. Undervoltage releases cannot be installed simultaneously with NZM...-XHIV... early-make auxiliary contact or NZM...-XA... shunt release.

10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function The device meets the requirements, provided the information in the....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2/3-XU600AC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.