

## INDUSTRIAL COMPONENT DATA

# 9PXM16KIRTN EATON ELECTRIC Eaton 9PX 16Ki 8Ki Redundant RT15U Netpack

Brand: EATON - MOELLER | Manufacturer Part Number: 9PXM16KIRTN



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | 9PXM16KIRTN     |
| Catalog number  | 10000           |
| Category        | UPS             |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-5BC7DB88D7   |
| Generated       | 2026-08-04      |

## Product Overview

Eaton 9PX 16Ki 8Ki Red. RT15U Netpack

Eaton 9PX 16Ki 8Ki Red. RT15U Netpack - Eaton 9PX 16Ki 8Ki Redundant RT15U Netpack

Eaton 9PX UPS 16Ki 8Ki Redundant Netpack, 16 kVA, 14.4 kW, Input: Hardwired, Outputs: (4) C19, Hardwired, Rack/tower, 15U, Network card included

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                |
|--------------|------------------------------------------------|
| Catalog path | EATON - MOELLER > Single-phase UPS up to 11kVA |
|--------------|------------------------------------------------|

## Additional Product Information

## General specifications

Product Name Eaton 9PX UPS Catalog Number 9PXM16KIRTN Model Code Eaton 9PX 16Ki 8Ki Red. RT15U Netpack  
UPC 743172045331 Product Length/Depth 70 cm Product Height 65 cm Product Width 44 cm Product Weight 183 kg

Compliances CE Marked

TUV Certifications IEC/EN 62040-1

IEC/EN 62040-2

CE

## EAC Product specifications

Special features Type UPS Topology Online/Double-conversion Form factor Rack/tower Rack size 15U Construction type 482.6 mm (19 inch) device Color Black/silver VA rating 16 kVA Wattage 14.4 kW Rack mounting kit Yes Package contents (2) UPS

ModularEasy

2 Connection cables from the UPS to the ModularEasy

DB15 Cable

(2) Network Management Card

Link plates

(2) Supports for tower mounting

(5) Rack-mounting kit

User manual

Internal bypass Yes Hot swap power Yes Auto shutdown function Yes Primary frequency - max 70 Hz Primary frequency - min 40 Hz Input connection Hardwired/fixed connection Input nominal voltage 230V default (200/208/220/230/240/250V)

Nominal frequency 50/60 Hz Input frequency range 40-70 Hz Input power factor >.99 Receptacle (4) C19, Hardwired

Number of Outputs C19 4 Number of outputs hardwired 1 Output waveform Sine wave Voltage 230V Output nominal voltage 230V default (200/208/220/230/240/250V) Feed type 1 Voltage type AC Runtime graph View runtime graph Battery management ABM & Temperature compensated charging method (user selectable)

Automatic battery test

Deep discharge protection

Automatic recognition of external battery units

Bat...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 9PXM16KIRTN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.