

INDUSTRIAL COMPONENT DATA

9PX6KIRTNP31 EATON ELECTRIC Eaton 9PX 6000i 3:1 RT6U HotSwap Netpack

Brand: EATON - MOELLER | Manufacturer Part Number: 9PX6KIRTNP31



Manufacturer	EATON - MOELLER
MPN / Reference	9PX6KIRTNP31
Catalog number	10000
Category	UPS
Minimum order	1 Pcs
Document ID	EO-86929BB11A
Generated	2026-08-05

Product Overview

Eaton 9PX 6000i 3:1 RT6U HotSwap Netpack

Eaton 9PX UPS 3:1 HotSwap Netpack, 6000 VA, 5400 W, Input: Hardwired, Outputs: (4) C19, Hardwired, Rack/tower, 6U, Network card included

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

General specifications

Product Name Eaton 9PX UPS Catalog Number 9PX6KIRTNP31 Model Code Eaton 9PX 6000i 3:1 RT6U HotSwap Netpack UPC 743172045256 Product Length/Depth 70 cm Product Height 26 cm Product Width 44 cm Product Weight 88 kg Compliances CE Marked

TUV Certifications IEC/EN 62040-1

IEC/EN 62040-2

CE

EAC Battery

Runtime graph Battery management Battery replacement Hot-swappable battery modules Battery quantity 20 Battery rating 12 V / 9 Ah Battery type Sealed, lead-acid Extended battery capability Yes Electrical output

Receptacle (4) C19, Hardwired Topology Online/Double-conversion Wattage 5400 W VA rating 6000 VA Output waveform Sine wave Voltage 400V Output power factor 0.9 Output nominal voltage 230V default (200/208/220/230/240V) Output voltage range 200/208/220/230/240 V +/- 1% Voltage distortion output (linear load) - max 2 Output frequency 50/60 Hz

Feed type 2 Electrical input

Input connection Hardwired/fixed connection Input nominal voltage 400V default (380/400/415V) Input voltage range

305-480 V Nominal frequency 50/60 Hz Input frequency range 40-70 Hz Input power factor >.99 Communications

Communication USB port (HID compliant)

Serial port (RS232)

Mini terminal block for remote On/Off

Mini-terminal block for remote power off

Dry contacts (4 outputs, relay, DB9)

Network card

Expansion slots One slot, network card included Ethernet interface Yes Includes network card Yes Software compatibility

Eaton Intelligent Power Manager, Eaton Intelligent Power Protect...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 9PX6KIRTNBP31 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.