

INDUSTRIAL COMPONENT DATA

Eaton 9PX 5000i RT3U Netpack 9PX5KIRTN EATON ELECTRIC

Eaton 9PX 5000i RT3U Netpack

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 5000i RT3U Netpack



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9PX 5000i RT3U Netpack
Catalog number	9PX5KIRTN
Category	UPS
Minimum order	1 Pcs
Document ID	EO-0ED5ECA4F4A
Generated	2026-08-02

Product Overview

Eaton 9PX 5000i RT3U Netpack

Eaton 9PX UPS Netpack, 5000 VA, 4500 W, Input: Hardwired, Outputs: (8) C13, (2) C19, Hardwired, Rack/tower, 3U, Network card included

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

General specifications

Product Name Eaton 9PX UPS Catalog Number 9PX5KIRTN Model Code Eaton 9PX 5000i RT3U Netpack UPC 743172040183 Product Length/Depth 68.5 cm Product Height 13 cm Product Width 44 cm Product Weight 48 kg
 Compliances CE Marked

TUV

cULus Listed

CSA 22.2 Certifications UL 1778

IEC/EN 62040-1

IEC/EN 62040-2

CE

EAC Battery

Runtime graph View runtime graph Battery management Battery replacement Hot-swappable internal batteries and extended battery modules (EBMs) Battery quantity 15 Battery rating 12 V / 5 Ah Battery type Sealed, lead-acid Extended

battery capability Yes Electrical output

Receptacle (8) C13, (2) C19, Hardwired Topology Online/Double-conversion Wattage 4500 W VA rating 5000 VA Output

waveform Sine wave Voltage 230V Output power factor 0.9 Output nominal voltage 230V default (200/208/220/230/240V)

Output voltage range 200/208/220/230/240 V +/- 1% Voltage distortion output (linear load) - max 2 Output frequency 50/60

Hz Feed type 1 Electrical input

Input connection Hardwired/fixed connection Input nominal voltage 230V default (200/208/220/230/240V) Input voltage range 176-276 V (100-276 V with derating) Nominal frequency 50/60 Hz Input frequency range 40-70 Hz Input power factor

>.99 Communications

Communication USB port (HID compliant)

Serial port (RS232)

Mini terminal block for remote On/Off

Mini-terminal block for remote power off

Dry contacts (4 outputs, relay, DB9)

DB15 for parallel operation

Network card

Expansion slots One slot, network card....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 5000i RT3U Netpack with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.