

INDUSTRIAL COMPONENT DATA

Eaton 9PX 6000i 3:1 HotSwap 9PX6KIBP31 9105-1201-KIT

EATON ELECTRIC Eaton 9PX 6000i 3:1 HotSwap

Brand: EATON - MOELLER | Manufacturer Part Number: Eaton 9PX 6000i 3:1 HotSwap



Manufacturer	EATON - MOELLER
MPN / Reference	Eaton 9PX 6000i 3:1 HotSwap
Catalog number	9105-1201-KIT
Category	UPS
Minimum order	1 Pcs
Document ID	EO-C80BB78F7F
Generated	2026-08-05

Product Overview

Eaton 9PX 6000i 3:1 HotSwap

Eaton 9PX UPS 3:1 HotSwap, 6000 VA, 5400 W, Input: Hardwired, Outputs: (4) C19, Hardwired, Rack/tower, 3U

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Single-phase UPS up to 11kVA**

Additional Product Information

General specifications

Product Name Eaton 9PX UPS Catalog Number 9PX6KIBP31 Model Code Eaton 9PX 6000i 3:1 HotSwap UPC 743172040282 Product Length/Depth 70 cm Product Height 44 cm Product Width 26 cm Product Weight 88 kg

Compliances CE Marked

TUV Certifications IEC/EN 62040-1

IEC/EN 62040-2

CE

EAC Battery

Runtime graph View runtime graph Battery management Battery replacement Hot-swappable battery modules Battery quantity 20 Battery rating 12 V / 9 Ah Battery type Sealed, lead-acid Extended battery capability Yes Electrical output Receptacle (4) C19, Hardwired Topology Online/Double-conversion Wattage 5400 W VA rating 6000 VA Output waveform Sine wave Voltage 400V Output power factor 0.9 Output nominal voltage 230V default (200/208/220/230/240V) Output voltage range 200/208/220/230/240 V +/- 1% Voltage distortion output (linear load) - max 2 Output frequency 50/60 Hz Feed type 2 Electrical input

Input connection Hardwired/fixed connection Input nominal voltage 400V default (380/400/415V) Input voltage range 305-480 V Nominal frequency 50/60 Hz Input frequency range 40-70 Hz Input power factor >.99 Communications Communication USB port (HID compliant) Serial port (RS232) Mini terminal block for remote On/Off Mini-terminal block for remote power off Dry contacts (4 outputs, relay, DB9) Expansion slots One slot for optional communication card Ethernet interface No Includes network card No Software compatibility Eaton Intelligent Power Manager, Eaton Intelligent Power Protector....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Eaton 9PX 6000i 3:1 HotSwap with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.