

INDUSTRIAL COMPONENT DATA

VGDILE415 010463 XTMCXVSN EATON ELECTRIC Varistor suppressor, 415VAC, for DILE, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: VGDILE415



Manufacturer	EATON - MOELLER
MPN / Reference	VGDILE415
Catalog number	XTMCXVSN
Category	Surge protection module
Minimum order	1 Pcs
Document ID	EO-D394320385
Generated	2026-08-03

Product Overview

Varistor suppressor, 415VAC, for DILE, screw connection

Varistor Suppressor Module 415 V AC Screw Connection For Contactor

Eaton Moeller® series DILE Varistor suppressor, 415VAC, for DILE, screw connection

Varistor suppressor circuit, Accessories: Suppressor circuit, Description: Varistor suppressor, Actuating voltage: Us 380 - 415 AC V, For use with: DILE...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > KDIL Accessories
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILE Accessory Varistor suppressor circuit Catalog Number 010463 Model Code VGDILE415 EAN 4015080104636 Product Length/Depth 16 mm Product Height 29 mm Product Width 33 mm Product Weight 0.01 kg Certifications CSA

CSA File No.: 012528

UL

CSA-C22.2 No. 14-05

IEC/EN 60947-4-1

CSA Class No.: 3211-03

UL File No.: E29096

CE

UL 508

UL Category Control No.: NLDX Features & Functions

Functions Varistor (voltage-sensitive resistor) General

Product category Accessories Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 380 V Rated control supply voltage (Us) at AC, 50 Hz - max 415 V

Rated control supply voltage (Us) at AC, 60 Hz - min 380 V Rated control supply voltage (Us) at AC, 60 Hz - max 415 V

Rated control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,

current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,

non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / VGDILE415 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.