

INDUSTRIAL COMPONENT DATA

DILM32-XSPVL240 281223 Y7-281223 EATON ELECTRIC

Varistor suppressor, +LED, 130-240VAC, for DILM17-32

Brand: EATON - MOELLER | Manufacturer Part Number: DILM32-XSPVL240



Manufacturer	EATON - MOELLER
MPN / Reference	DILM32-XSPVL240
Catalog number	Y7-281223
Category	Surge protection module
Minimum order	10 Pcs
Document ID	EO-3D3203988C
Generated	2026-08-06

Product Overview

Varistor suppressor, +LED, 130-240VAC, for DILM17-32

DILM32-XSPVL240

Eaton Moeller® series DILM Varistor suppressor circuit, 130 - 240 AC V, For use with: DILM17 - DILM32, DILK12 - DILK25, DILL..., DILMP32 - DILMP45 DILM32-XSPVL240

Varistor suppressor circuit, Accessories: Suppressor circuit, Voltage: Us 130 - 240 AC V, For use with: DILM17 - DILM32, DILK12 - DILK25, DILL..., DILMP32 - DILMP45

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM varistor suppressor circuit Catalog Number 281223 Model Code

DILM32-XSPVL240 EAN 4015082812232 Product Length/Depth 45 mm Product Height 25 mm Product Width 9 mm

Product Weight 0.006 kg Certifications UL Recognized

CSA

CSA-C22.2 No. 14-05

UL Category Control No.: NKCR2, NKCR8

CSA File No.: 256465

CE

IEC/EN 60947-4-1

UL 508

UL File No.: E29184

CSA Class No.: 3211-07 Catalog Notes With DC operated contactors and with DILM115 and DILM150 the suppressor is integrated. Features & Functions

Functions Varistor (voltage-sensitive resistor) Fitted with: LED indication General

Product category Accessories Used with DILL... and DILM32-XSPVL240 Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 130 V Rated control supply voltage (Us) at AC, 50 Hz - max 240 V

Rated control supply voltage (Us) at AC, 60 Hz - min 130 V Rated control supply voltage (Us) at AC, 60 Hz - max 240 V

Rated control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Rated operational current for specified heat dissipation (I_n) 0 A 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM32-XSPVL240 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.