

INDUSTRIAL COMPONENT DATA

BP-MSL-MSW-12-W 111429 EATON ELECTRIC Vertical/Middle add-on connection Element MSW H 1260mm, white

Brand: EATON - MOELLER | Manufacturer Part Number: BP-MSL-MSW-12-W



Manufacturer	EATON - MOELLER
MPN / Reference	BP-MSL-MSW-12-W
Catalog number	111429
Category	Component for installation (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-B21ECF4842
Generated	2026-08-02

Product Overview

Vertical/Middle add-on connection Element MSW H=1260mm, white

Vertical/center add-on element, BP-MSL-MSW, height 1260mm, vertical add-on element between 2 distribution boards installed next to each other, includes screws for using MSW assembly side panels, for surface-mounted distribution board IP30, add-on configuration with BPZ-SP-...-MSW side panel, 1 kit of side panels, used for add-on configurations, to get the max. door opening angle, the left distribution board must have a door that closes on the left and the right distribution board must have a door that closes on the right, can be combined with BP-MFL for horizontal distribution board mounting, material characteristic: sheet steel , powder-spray painted, RAL 9016, equipment supplied: 1 add-on element, 2 mounting elements, various mounting accessories

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Fuse-link, low voltage, 12 A, AC 600 V, DC 170 V, 33.3 x 10.4 mm, G, UL, CSA, time-delay Fuse, Fuse-link, low voltage, 12 A, AC 600 V, DC 170 V, 33.3 x 10.4 mm, G, UL, CSA, time-delay, cylindrical, size-rejecting, fusible branch panelboards, HVAC branch circuit protection, UL 248-5, Breaking Capacity 100 kA, time-delay 12 seconds (minimum) at 200% of rated current [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 12 A Rated voltage AC 600 V DC 170 V Size 33.3 x 10.4 mm Utilization category G Description size-rejecting Breaking Capacity 100 kA usable for size/applications fusible branch panelboards, HVAC branch circuit protection Release characteristic [class] time-delay Standard/Approval UL

CSA Shape cylindrical Standards/Regulations UL 248-5 Time delay time-delay 12 seconds (minimum) at 200% of rated current , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) () [AFZ797013]) Size Other Rated voltage 600 - 600 V Rated voltage Other Voltage type AC/DC Utilization category Other Rated operating frequency 45 - 62 Hz Nominal current 12 A With striker No Release characteristic G Breaking capacity 100 kA]

ETIM for 111429 Cabinets and enclosures (EC002620)

Feature Name

Feature Value

Model (EF000010)

Mounting kit....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-MSL-MSW-12-W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.