

INDUSTRIAL COMPONENT DATA

VGDILE48-C 230265 XTMCXVSCW EATON ELECTRIC Varistor suppressor, 48VAC, for DILE, spring clamp connection

Brand: EATON - MOELLER | Manufacturer Part Number: VGDILE48-C



Manufacturer	EATON - MOELLER
MPN / Reference	VGDILE48-C
Catalog number	XTMCXVSCW
Category	Surge protection module
Minimum order	10 Pcs
Document ID	EO-D88C607772
Generated	2026-08-03

Product Overview

Varistor suppressor, 48VAC, for DILE, spring clamp connection

VGDILE48-C

Eaton Moeller® series DILE Varistor suppressor, 48VAC, for DILE, spring clamp connection

Varistor suppressor circuit, Accessories: Suppressor circuit, Description: Varistor suppressor, Actuating voltage: Us 24 - 48 AC V, For use with: DILE...-C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > KDIL Accessories
--------------	------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILE Accessory Varistor suppressor circuit Catalog Number 230265 Model Code VGDILE48-C EAN 4015082302658 Product Length/Depth 16 mm Product Height 29 mm Product Width 33 mm Product Weight 0.009 kg Certifications CSA-C22.2 No. 14-05

CE

UL

CSA

IEC/EN 60947-4-1

CSA Class No.: 3211-03

CSA File No.: 012528

UL File No.: E29096

UL 508

UL Category Control No.: NLDX Features & Functions

Functions Varistor (voltage-sensitive resistor) General

Product category Accessories Used with DILE...-C Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 48 V Rated control supply voltage (Us) at AC, 50 Hz - max 48 V Rated

control supply voltage (Us) at AC, 60 Hz - min 48 V Rated control supply voltage (Us) at AC, 60 Hz - max 48 V Rated

control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,

current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,

non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verificati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / VGDILE48-C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.