

INDUSTRIAL COMPONENT DATA

VLC14-2P 285363 EATON ELECTRIC Fuse switch-disconnector, 50A, 2p, 14x51 size

Brand: EATON - MOELLER | Manufacturer Part Number: VLC14-2P



Manufacturer	EATON - MOELLER
MPN / Reference	VLC14-2P
Catalog number	285363
Category	Fuse switch disconnector
Minimum order	1 Pcs
Document ID	EO-6EBA42AF13
Generated	2026-08-05

Product Overview

Fuse switch-disconnector, 50A, 2p, 14x51 size

The flash function indicates the blowing of fuse link. rated operating voltage 690 VAC, suitable for cylindrical fuse links with utilization class gG (gL), aM, can be sealed, double conductor run possible on both sides

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Modular Switchgear - Others and Accessories**

Additional Product Information

Fuse switch-disconnector, 50A, 2p, 14x51 size The flash function indicates the blowing of fuse link. rated operating voltage 690 VAC, suitable for cylindrical fuse links with utilization class gG (gL), aM, can be sealed, double conductor run possible on both sides [Delivery program

For cylindrical fuses Up to 50 A

Without flashing function Size 14 x 51 Number of poles 2 pole , Technical data

Electrical Number of poles 1P

1P+N

2P

3P

3P+N Rated operating voltage [Ue] 690 V AC Rated operational current [Ie] 50 A Rated conditional short-circuit current [Ie] 100 Rated frequency [f] 50 Hz Utilization category AC 22 B Rated impulse withstand voltage [Uimp] 8 kV Fuse gG: 5, aM: 3 W Mechanical Standard front dimension 45 mm Enclosure height 94 mm Mounting width 27/per pole mm Weight 1P 100 1P+N 222

2P 201

3P 308

3P+N 437 g Mounting Quick attachment for top-hat rail IEC/EN 60715 Degree of protection Integrated IP20 Terminals Lift terminals Terminal capacities Solid 1.5 - 35 mm² Temperature range -25 ... +60 °C Specified tightening torque for terminal screws Tightening torque max. 2 Nm Overvoltage category/pollution degree -/1 Track resistance CTI 400 , Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [In] 50 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 10 W Static heat dissipation, non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdis] 0 W Operating ambient temperat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / VLC14-2P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.