

INDUSTRIAL COMPONENT DATA

VLCE14-1P/L 192374 Y7-192374 EATON ELECTRIC Fuse switch-disconnector, 50A, 1p, 22x51 size

Brand: EATON - MOELLER | Manufacturer Part Number: VLCE14-1P/L



Manufacturer	EATON - MOELLER
MPN / Reference	VLCE14-1P/L
Catalog number	Y7-192374
Category	Fuse switch disconnector
Minimum order	1 Pcs
Document ID	EO-FB98D5F9B8
Generated	2026-08-05

Product Overview

Fuse switch-disconnector, 50A, 1p, 22x51 size

VLCE14-1P/L

Eaton Distribution parts. Fuse switch-disconnector, 50A, 1p, 22x51 size, L

The flash function indicates the blowing of fuse link. rated operating voltage 690 VAC, suitable for cylindrical fuse links with utilization class gG (gL), aM, can be sealed, double conductor run possible on both sides

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 192374 Model Code VLCE14-1P/L EAN 4015081929252 Product Length/Depth 75.8 mm Product Height 94 mm Product Width 27 mm Product Weight 0.103 kg Compliances RoHS conform Product specifications

Type Fuse material Special features Features Version as safety switch Frame Standard front dimension: 45 mm Frequency rating 50 Hz Pollution degree 1 Creepage resistance CTI 400 Rated uninterrupted current (Iu) 50 A Terminals Lift terminals Conditioned rated short-circuit current Iq 100 kA Number of poles Single-pole Rated operation power at AC-23, 400 V 0 kW Size 14 mm x 51 mm Rated impulse withstand voltage (Uimp) 8 kV Utilization category AC-22 B Degree of protection IP20 Rated short-time withstand current (Icw) 0.6 kA Electrical connection type of main circuit Screw connection Actuator position Front side Actuator type Rocker lever Ambient operating temperature - max 55 °C Ambient operating temperature - min -25 °C Enclosure width 94 mm Suitable for Ground mounting Rated conditional short-circuit current (Iq) 100 kA Functions Fuse

switch-disconnector VLC..., empty Suitable for fuses 14x51 mm Cable entry type Other Mounting method Quick attachment for top-hat rail IEC/EN 60715 Rated operation current (Ie) 50 A Voltage rating 690 V AC Degree of protection (front side) IP20 Mounting width 27 mm per pole (1.5 space units) Terminal capacity (solid cable) 1.5 mm² - 10 mm² Permitted heat loss from fuse links - max gG:....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / VLCE14-1P/L with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.