

INDUSTRIAL COMPONENT DATA

VLCE22-1P 192380 Y7-192380 EATON ELECTRIC Fuse switch-disconnector, 100A, 1p, 22x58 size

Brand: EATON - MOELLER | Manufacturer Part Number: VLCE22-1P



Manufacturer	EATON - MOELLER
MPN / Reference	VLCE22-1P
Catalog number	Y7-192380
Category	Fuse switch disconnector
Minimum order	1 Pcs
Document ID	EO-4A409D669A
Generated	2026-08-06

Product Overview

Fuse switch-disconnector, 100A, 1p, 22x58 size

VLCE22-1P

Eaton Distribution parts. Fuse switch-disconnector, 100A, 1p, 22x58 size

The flash function indicates the blowing of fuse link. rated operating voltage 690 VAC, suitable for cylindrical fuse links with utilization class gG (gL), aM, can be sealed, double conductor run possible on both sides

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 192380 Model Code VLCE22-1P EAN 4015081929313 Product Length/Depth 75.8 mm Product Height 120.4 mm Product Width 35.6 mm Product Weight 0.156 kg Compliances RoHS conform Product specifications

Type Fuse material Special features Features Version as safety switch Frame Standard front dimension: 45 mm Frequency rating 50 Hz Pollution degree 1 Creepage resistance CTI 400 Rated uninterrupted current (Iu) 50 A Terminals Lift terminals Conditioned rated short-circuit current Iq 100 kA Number of poles Single-pole Rated operation power at AC-23, 400 V 0 kW Size 22 mm x 58 mm Rated impulse withstand voltage (Uimp) 8 kV Utilization category AC-21 B Degree of protection IP20 Rated short-time withstand current (Icw) 0.6 kA Electrical connection type of main circuit Screw connection Actuator position Front side Actuator type Rocker lever Ambient operating temperature - max 55 °C Ambient operating temperature - min -25 °C Enclosure width 121 mm Suitable for Ground mounting Rated conditional short-circuit current (Iq) 100 kA Functions Fuse

switch-disconnector VLC..., empty Suitable for fuses 22x58 mm Cable entry type Other Mounting method Quick attachment for top-hat rail IEC/EN 60715 Rated operation current (Ie) 100 A Voltage rating 690 V AC Degree of protection (front side) IP20 Mounting width 36 mm per pole Terminal capacity (solid cable) 2.5 mm² - 35 mm² (1x) Permitted heat loss from fuse links - max gG: 9.5 W, a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / VLCE22-1P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.