

INDUSTRIAL COMPONENT DATA

BPZ-WB3S-400/12/2 111126 EATON ELECTRIC Wall trough for three-component system HxWxD 1260x400x240mm

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-WB3S-400/12/2



Manufacturer	EATON - MOELLER
MPN / Reference	BPZ-WB3S-400/12/2
Catalog number	111126
Category	Component for installation (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-5CB6C62C85
Generated	2026-08-06

Product Overview

Wall trough for three-component system HxWxD=1260x400x240mm

Wall trough, for 3 steps system, BPZ-WB3S, width 400 mm, height 1260mm, depth 240 mm, knockout that is easy to knock out, designed for installation in 3-component flush-mounted door frame, material characteristic: sheet steel, zinc coated, equipment supplied: 1 wall trough, various mounting accessories

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Fuse-link, LV, 2 A, AC 400 V, NH000, gL/gG, IEC, dual indicator, insulated gripping lugs Fuse, fuse-link, low voltage, 2 A, AC 400 V, NH000, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, insulated gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA [Delivery program
Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 2 A Rated voltage AC 400 V
Construction size NH000 Utilization category gL/gG Status indicator dual (combination) indicator system Description
insulated gripping lugs Breaking Capacity 120 kA Standard/Approval IEC Shape square body with knife blade contacts
Standards/Regulations IEC 60269-2 fuse system A
DIN 43620
VDE 0636-2 , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015]) Construction size NH000 Rated current 2 A Rated voltage 400 V Voltage type AC Rated switching capacity

120 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator Combination fuse status indicator Insulated metal gripping lugs (IMGL) Yes]

ETIM for 111126 Cabinets and enclosures (EC002620)

Feature Name

Feature Value

Model (EF000010)

Other

Suitable for enclosure building width (EF000326)

400 mm

Suitable for encl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-WB3S-400/12/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.