

## INDUSTRIAL COMPONENT DATA

**BPZ-WB3S-600/20/1 111107 EATON ELECTRIC Wall trough for three-component system HxWxD 2060x600x180mm**

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-WB3S-600/20/1



|                 |                                                 |
|-----------------|-------------------------------------------------|
| Manufacturer    | EATON - MOELLER                                 |
| MPN / Reference | BPZ-WB3S-600/20/1                               |
| Catalog number  | 111107                                          |
| Category        | Component for installation (switchgear cabinet) |
| Minimum order   | 1 Pcs                                           |
| Document ID     | EO-7A6DB705F3                                   |
| Generated       | 2026-08-05                                      |

**Product Overview**

Wall trough for three-component system HxWxD=2060x600x180mm

Wall trough, for 3 steps system, BPZ-WB3S, width 600 mm, height 2060mm, depth 180 mm, knockout that is easy to knock out, designed for installation in 3-component flush-mounted door frame, material characteristic: sheet steel, zinc coated, equipment supplied: 1 wall trough, various mounting accessories

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |                 |
|--------------|-----------------|
| Catalog path | EATON - MOELLER |
|--------------|-----------------|

**Additional Product Information**

Fuse-link, low voltage, 600 A, AC 300 V, DC 160 V, 77.8 x 31.8, T, UL, very fast acting Fuse, Fuse-link, low voltage, 600 A, AC 300 V, DC 160 V, 77.8 x 31.8, T, UL, very fast acting, Breaking Capacity 200 kA [ Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 600 A Rated voltage DC 160 V Size 77.8 x 31.8 Utilization category T Breaking Capacity 20 kA Release characteristic [class] very fast acting Standard/Approval UL , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected] [AFZ800015]) Construction size Other Rated current 600 A Rated voltage 300 V Voltage type AC/DC Rated switching capacity 200 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No ] ETIM for 111107 Cabinets and enclosures (EC002620)

Feature Name

Feature Value

Model (EF000010)  
Other  
Suitable for enclosure building width (EF000326)  
600 mm  
Suitable for enclosure building height (EF009583)  
2060 mm  
Suitable for enclosure building depth (EF000327)  
180 mm  
Width (EF000008)  
100 mm  
Height (EF000040)  
2030 mm  
Depth (EF000049)  
185 mm  
Max. load capacity (EF000258)  
0 kg  
Material (EF002169)  
Metal  
Colour (EF000007)  
Stainless steel  
RAL-number (EF000116)  
0

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-WB3S-600/20/1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.