

INDUSTRIAL COMPONENT DATA

BPZ-WBO2S-1000/15/2 293388 EATON ELECTRIC Wall box open for 2-step system HxWxD 1500x1000x240mm

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-WBO2S-1000/15/2



Manufacturer	EATON - MOELLER
MPN / Reference	BPZ-WBO2S-1000/15/2
Catalog number	293388
Category	Component for installation (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-6F9EA31143
Generated	2026-08-05

Product Overview

Wall box open for 2-step system HxWxD=1500x1000x240mm

Wall trough, open for 2-component system, BPZ-WBO2S, width 1000 mm, height 1500mm, depth 240 mm, knockout that is easy to knock out, designed for installation in 2-component flush-mounted door frame, material characteristic: sheet steel, zinc coated, equipment supplied: 1 wall trough, various mounting accessories

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Reversing multi-speed switches, Contacts: 10, 32 A, 2 speeds, 2 separate windings, front plate: 2-1-0-1-2, 60 °, maintained, flush mounting Reversing multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Contacts: 10, Degree of Protection: Front IP65, Design: flush mounting, switching function: 2 speeds, 2 separate windings, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-1-0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3 [Delivery program Product range Control switches Part group reference T3 Basic function Reversing multi-speed switches with black thumb grip and front plate Contacts 10 Degree of Protection Front IP65 Design flush mounting Contact sequence switching function 2 speeds, 2 separate windings Switching angle 60 ° Switching performance maintained With 0 (Off) position Front plate no. front plate 2-1-0-1-2 Motor rating AC-23A, 50 - 60 Hz [P] 400 V [P] 15 kW Rated uninterrupted current [I_u] 32 A Note on rated uninterrupted current I_u Rated uninterrupted current I_u is specified for max. cross-section. Number of contact units 5 contact unit(s) , Technical data

General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL
Switch-disconnector according to IEC/EN 60947-3 Climatic proofing...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-WBO2S-1000/15/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.