

**INDUSTRIAL COMPONENT DATA**

# BPZ-WBO2S-600/15/1 293365 EATON ELECTRIC Wall box open for 2-step system HxWxD 1500x600x180mm

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-WBO2S-600/15/1



|                 |                                                 |
|-----------------|-------------------------------------------------|
| Manufacturer    | EATON - MOELLER                                 |
| MPN / Reference | BPZ-WBO2S-600/15/1                              |
| Catalog number  | 293365                                          |
| Category        | Component for installation (switchgear cabinet) |
| Minimum order   | 1 Pcs                                           |
| Document ID     | EO-4AB368E112                                   |
| Generated       | 2026-08-06                                      |

## Product Overview

Wall box open for 2-step system HxWxD=1500x600x180mm

Wall trough, open for 2-component system, BPZ-WBO2S, width 600 mm, height 1500mm, depth 180 mm, knockout that is easy to knock out, designed for installation in 2-component flush-mounted door frame, material characteristic: sheet steel, zinc coated, equipment supplied: 1 wall trough, various mounting accessories

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                 |
|--------------|-----------------|
| Catalog path | EATON - MOELLER |
|--------------|-----------------|

## Additional Product Information

Pushbutton, classic, flat, taster, 1 N/C, cable (black) with non-terminated end, 4 pole, 1 m Pushbutton, RMQ compact solution, Complete unit, Design: Flat, momentary, Connection type: Cable (black) with non-terminated end, 4 pole, Cable Length: 1 m, button plate: Without button plate, Degree of Protection: IP66, IP67, IP69K (front), IP65 (on rear), Bezel: titanium, Connection to SmartWire-DT: no, Contacts N/C = Normally closed: 1 NC, Contacts Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Actuator travel and actuation force as per DIN EN 60947-5-1, K.5.4.1: mm 4.65, Maximum travel: mm 5.7, Minimum force for positive opening: N 15, Positive opening (ZW): yes, Standards: IEC/EN 60947-5-1, VDE 0660 [ Delivery program

Product range RMQ compact solution Basic function Pushbutton actuators Single unit/Complete unit Complete unit Design Flat momentary Connection type Cable (black) with non-terminated end, 4 pole Cable Length 1 m Button plate button plate Without button plate Degree of Protection IP66, IP67, IP69 (front)

IP65 (on rear) Front ring Bezel: titanium Connection to SmartWire-DT no Contacts N/C = Normally closed 1 NC Notes = safety function, by positive opening to IEC/EN 60947-5-1 Actuator travel and actuation force as per DIN EN 60947-5-1,

K.5.4.1 [mm] 4.65 Maximum travel [mm] 5.7 Minimum force for positive opening [ N] 15 Contact sequence Contact travel? =  
Contact closed? = Contact open Contact diagram Positive opening (ZW) yes , Technical data  
Genera...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-WBO2S-600/15/1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.