

INDUSTRIAL COMPONENT DATA

BPZ-WBO2S-400/7/1 293351 AT4/11-1/I/V EATON ELECTRIC
Wall box open for 2-step system HxWxD 700x400x180mm

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-WBO2S-400/7/1



Manufacturer	EATON - MOELLER
MPN / Reference	BPZ-WBO2S-400/7/1
Catalog number	AT4/11-1/I/V
Category	Component for installation (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-3E9932DB88
Generated	2026-08-05

Product Overview

Wall box open for 2-step system HxWxD=700x400x180mm

Wall trough, open for 2-component system, BPZ-WBO2S, width 400 mm, height 700mm, depth 180 mm, knockout that is easy to knock out, designed for installation in 2-component flush-mounted door frame, material characteristic: sheet steel, zinc coated, equipment supplied: 1 wall trough, various mounting accessories

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Position switch, 1N/O+1N/C, narrow, IP65_x, adjustable roller lever Alternate Catalog No. AT4/11-1/I/V Position switch, Basic function: Position switches, Safety position switches, Part group reference: AT4, Product range: Adjustable roller lever, Degree of Protection: IP65, Features: Complete unit, Ambient temperature: -25 - +70 °C, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Notes: = safety function, by positive opening to IEC/EN 60947-5-1, Positive opening (ZW): yes, Colour Enclosure covers: Grey, Housing: Insulated material, Connection type: Screw terminal, Standards: IEC/EN 60947 [Delivery program

Basic function Position switches

Safety position switches Part group reference AT4 Product range Adjustable roller lever Degree of Protection IP65 Features Complete unit Ambient temperature -25 - +70 °C Approval Contacts N/O = Normally open 1 N/O N/C = Normally closed 1 NC Notes = safety function, by positive opening to IEC/EN 60947-5-1 Contact sequence Contact travel? = Contact closed? = Contact open Positive opening (ZW) yes Colour Enclosure covers Grey Enclosure covers Housing Insulated material Connection type Screw terminal Notes The operating head can be rotated at 90° intervals to adapt to the specified

approach direction.

For degree of protection IP65, use V-M20 (206910) cable glands with connecting thread of max. 9 mm length. , Technical data

General Standards IEC/EN 60947 Climatic proofing Damp heat, constant, to IEC 60068-2-78; damp h...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-WBO2S-400/7/1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.