

**INDUSTRIAL COMPONENT DATA**

# BPZ-WBO2S-400/7/2 293352 EATON ELECTRIC Wall box open for 2-step system HxWxD 700x400x240mm

Brand: EATON - MOELLER | Manufacturer Part Number: BPZ-WBO2S-400/7/2



|                 |                                                 |
|-----------------|-------------------------------------------------|
| Manufacturer    | EATON - MOELLER                                 |
| MPN / Reference | BPZ-WBO2S-400/7/2                               |
| Catalog number  | 293352                                          |
| Category        | Component for installation (switchgear cabinet) |
| Minimum order   | 1 Pcs                                           |
| Document ID     | EO-761BFE3078                                   |
| Generated       | 2026-08-05                                      |

## Product Overview

Wall box open for 2-step system HxWxD=700x400x240mm

Wall trough, open for 2-component system, BPZ-WBO2S, width 400 mm, height 700mm, depth 240 mm, knockout that is easy to knock out, designed for installation in 2-component flush-mounted door frame, material characteristic: sheet steel, zinc coated, equipment supplied: 1 wall trough, various mounting accessories

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                 |
|--------------|-----------------|
| Catalog path | EATON - MOELLER |
|--------------|-----------------|

## Additional Product Information

Reversing multi-speed switches, Contacts: 13, 32 A, One tapped winding, 2 speeds, front plate: 2-1-0-1-2, 60 °, maintained, flush mounting, SOND 30 Reversing multi-speed switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 30, Contacts: 13, Degree of Protection: Front IP65, Design: flush mounting, switching function: One tapped winding, 2 speeds, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-1-0-1-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I<sub>u</sub> = 32 A, 7 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3 [ Delivery program

Product range Control switches Part group reference T3 Basic function Reversing multi-speed switches with black thumb grip and front plate Notes SOND 30 Contacts 13 Degree of Protection Front IP65 Design flush mounting Contact sequence switching function One tapped winding

2 speeds Switching angle 60 ° Switching performance maintained

With 0 (Off) position Front plate no. front plate 2-1-0-1-2 Motor rating AC-23A, 50 - 60 Hz [P] 400 V [P] 15 kW Rated

uninterrupted current [I<sub>u</sub>] 32 A Note on rated uninterrupted current I<sub>u</sub> Rated uninterrupted current I<sub>u</sub> is specified for max. cross-section. Number of contact units 7 contact unit(s) , Technical data  
General Standards IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL  
Switch-disconnector according....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPZ-WBO2S-400/7/2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.