

## INDUSTRIAL COMPONENT DATA

# CS-108/300 111715 Y7-111715 EATON ELECTRIC Wall enclosure, +mounting plate, HxWxD 1000x800x300mm

Brand: EATON - MOELLER | Manufacturer Part Number: CS-108/300



|                 |                                      |
|-----------------|--------------------------------------|
| Manufacturer    | EATON - MOELLER                      |
| MPN / Reference | CS-108/300                           |
| Catalog number  | Y7-111715                            |
| Category        | Enclosure/switchgear cabinet (empty) |
| Minimum order   | 1 Pcs                                |
| Document ID     | EO-60217B640F                        |
| Generated       | 2026-08-05                           |

## Product Overview

Wall enclosure, +mounting plate, HxWxD=1000x800x300mm

CS-108/300

Wall-mounting enclosure CS, door with continuous foamed-in polyurethane gasket, shock resistance category IK09 to EN 62262, single door, door hinges right, opening angle 120°, door hinge pins with quick change technology, door profile molding with perforation at 25 mm intervals for fixing DIN mounting rails or for fixing cable conduits and leads, standardized locking system with sash fastener, made completely of metal, 3-point locking system with sheet steel mounting plate , equipment supplied: lock, 3mm double ward key. Optional accessory equipment e.g. rotary comfort grip PHZ-A-ADD-ON with cylinder lock PHZ-E10/30-GS . Designed according IEC/EN 62208.

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                              |
|--------------|------------------------------|
| Catalog path | EATON - MOELLER > Enclosures |
|--------------|------------------------------|

## Additional Product Information

Wall enclosure with mounting plate, HxWxD=1000x800x300mmWall-mounting enclosure CS, door with continuous foamed-in polyurethane gasket, shock resistance category IK09 to EN 62262, single door, door hinges right, opening angle 120°, door hinge pins with quick change technology, door profile molding with perforation at 25 mm intervals for fixing DIN mounting rails or for fixing cable conduits and leads, standardized locking system with sash fastener, made completely of metal, 3-point locking system with sheet steel mounting plate , equipment supplied: lock, 3mm double ward key. Optional accessory equipment e.g. rotary comfort grip PHZ-A-ADD-ON with cylinder lock PHZ-E10/30-GS . Designed according IEC/EN 62208.

General specificationsProduct nameEaton xEffect CS enclosure single doorPart

no.CS-108/300EAN4015081112746Product Length/Depth300 millimetreProduct height1000 millimetreProduct width800 millimetreProduct weight56.8 kilogramCompliancesUL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the back sheet metal enclosure)

RoHS conform

UL 508A; CSA-C22.2 No.14; IEC/EN 62208; CE markingCertificationsIEC Rated IEC/EN 60529

UL Listed

UL 508A

CSA Std. C22.2 No. 14

IEC/EN 62208

UL (File No. E336299)

UL CSA08 (request filed)

UL (Category Control Number NITW)

In accordance with Directive 2015/863/EU of the European Parliament and CouncilProduct TradenamexEffect CSProduct TypeEnclosureProduct Sub TypeSingle doorCatalog NotesFoame...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CS-108/300 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.