

INDUSTRIAL COMPONENT DATA

CS-33/150 111648 Y7-111648 EATON ELECTRIC Wall enclosure, +mounting plate, HxWxD 300x300x150mm

Brand: EATON - MOELLER | Manufacturer Part Number: CS-33/150



Manufacturer	EATON - MOELLER
MPN / Reference	CS-33/150
Catalog number	Y7-111648
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-B9E9C3B782
Generated	2026-08-05

Product Overview

Wall enclosure, +mounting plate, HxWxD=300x300x150mm

CS-33/150

Eaton xEffect CS LV systems Switch- & Controlgear Enclosure. Wall enclosure with mounting plate, HxWxD=300x300x150mm

Wall-mounting enclosure CS, door with continuous foamed-in polyurethane gasket, shock resistance category IK09 to EN 62262, single door, door hinges right, opening angle 120°, door hinge pins with quick change technology, door profile molding with perforation at 25 mm intervals for fixing DIN mounting rails or for fixing cable conduits and leads, standardized locking system with sash fastener, made completely of metal, with mounting plate sheet steel, equipment supplied: lock, 3mm double ward key. Optional accessory equipment e.g. rotary comfort grip PHZ-A-ADD-ON with cylinder lock PHZ-E10/30-GS. Designed according IEC/EN 62208.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Enclosures**

Additional Product Information

General specifications

Product Name Eaton xEffect CS enclosure single door Catalog Number 111648 Model Code CS-33/150 EAN

4015081112074 Product Length/Depth 150 mm Product Height 300 mm Product Width 300 mm Product Weight 5.61 kg

Compliances UL 508A; CSA-C22.2 No.14; IEC/EN 62208; CE marking

RoHS conform

UL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the

back sheet metal enclosure) Certifications UL (Category Control Number NITW)

UL (File No. E336299)

IEC/EN 62208

UL CSA08 (request filed)

In accordance with Directive 2015/863/EU of the European Parliament and Council Product specifications

Special features Enclosed, foamed gasketFoamed polyurethane sealing throughout.Impact resistance category IK09 to EN 62262.Sheet steel mounting plateBottom plate with foamed gasket.Single door, door stop on the right, door opening angle 120°Door hinge pins with quick change technology.Standardized locking system with sash fastener.Lock, 3 mm double ward keyIncluding M6 threaded welded studs for earth conductor connections in the doorPowder coating RAL 7035 inside and outsideSide plates without aperturesTop plate without apertures Type Wall-mounting housing CSWall-mounting housing with mounting plate Features Wall build in

Pole fastening 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel bui...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CS-33/150 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.