

INDUSTRIAL COMPONENT DATA

CS-44/150 111683 Y7-111683 EATON ELECTRIC Wall enclosure, +mounting plate, HxWxD 400x400x150mm

Brand: EATON - MOELLER | Manufacturer Part Number: CS-44/150



Manufacturer	EATON - MOELLER
MPN / Reference	CS-44/150
Catalog number	Y7-111683
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-7FAE300995
Generated	2026-08-05

Product Overview

Wall enclosure, +mounting plate, HxWxD=400x400x150mm

CS-44/150

Eaton xEffect CS LV systems Switch- & Controlgear Enclosure. Wall enclosure with mounting plate, HxWxD=400x400x150mm

Wall-mounting enclosure CS, door with continuous foamed-in polyurethane gasket, shock resistance category IK09 to EN 62262, single door, door hinges right, opening angle 120°, door hinge pins with quick change technology, door profile molding with perforation at 25 mm intervals for fixing DIN mounting rails or for fixing cable conduits and leads, standardized locking system with sash fastener, made completely of metal, with mounting plate sheet steel, equipment supplied: lock, 3mm double ward key. Optional accessory equipment e.g. rotary comfort grip PHZ-A-ADD-ON with cylinder lock PHZ-E10/30-GS. Designed according IEC/EN 62208.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

General specifications

Product Name Eaton xEffect CS enclosure single door Catalog Number 111683 Model Code CS-44/150 EAN 4015081112425 Product Length/Depth 150 mm Product Height 400 mm Product Width 400 mm Product Weight 8.72 kg Compliances UL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the back sheet metal enclosure) RoHS conform

UL 508A; CSA-C22.2 No.14; IEC/EN 62208; CE marking Certifications UL (Category Control Number NITW)

In accordance with Directive 2015/863/EU of the European Parliament and Council

UL (File No. E336299)

IEC/EN 62208

UL CSA08 (request filed) Delivery program

Type Wall-mounting housing CSWall-mounting housing with mounting plate Color Gray

Light gray (RAL 7035) Technical data - mechanical

Design type Canted and seam welded, including two M6 threaded bolts for earth conductor connections inside the enclosure. Surface finishing Powder coating

Semi-textured

Structured powder spray polyester based paint finish

Gloss Surface treatment Structured powder spray polyester based paint finish Mounting method Wall fastening

9 mm drilling dimensions for wall mounting (Back plate)

Intermediate mounting Mounting plate height 370 mm Mounting plate material Sheet steel, hot-galvanized Mounting plate width 350 mm Material Steel

Steel plate Material thickness (body) 1.2 mm Material thickness (bottom plate) 2 mm Material thickness (door) 1.2 mm

Material quality Other Degree of protection IP66

IEC: IP66, indoo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CS-44/150 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.