

INDUSTRIAL COMPONENT DATA

CS-46/300 111687 Y7-111687 EATON ELECTRIC Wall enclosure, +mounting plate, HxWxD 400x600x300mm

Brand: EATON - MOELLER | Manufacturer Part Number: CS-46/300



Manufacturer	EATON - MOELLER
MPN / Reference	CS-46/300
Catalog number	Y7-111687
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-479D8312F0
Generated	2026-08-05

Product Overview

Wall enclosure, +mounting plate, HxWxD=400x600x300mm

CS-46/300

Eaton xEffect CS LV systems Switch- & Controlgear Enclosure. Wall enclosure with mounting plate, HxWxD=400x600x300mm

Wall-mounting enclosure CS, door with continuous foamed-in polyurethane gasket, shock resistance category IK09 to EN 62262, single door, door hinges right, opening angle 120°, door hinge pins with quick change technology, door profile molding with perforation at 25 mm intervals for fixing DIN mounting rails or for fixing cable conduits and leads, standardized locking system with sash fastener, made completely of metal, with mounting plate sheet steel, equipment supplied: lock, 3mm double ward key. Optional accessory equipment e.g. rotary comfort grip PHZ-A-ADD-ON with cylinder lock PHZ-E10/30-GS. Designed according IEC/EN 62208.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

General specifications

Product Name Eaton xEffect CS enclosure single door Catalog Number 111687 Model Code CS-46/300 EAN 4015081112463 Product Length/Depth 300 mm Product Height 400 mm Product Width 600 mm Product Weight 15.89 kg Compliances UL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the back sheet metal enclosure) UL 508A; CSA-C22.2 No.14; IEC/EN 62208; CE marking

RoHS conform Certifications IEC/EN 62208

In accordance with Directive 2015/863/EU of the European Parliament and Council

UL CSA08 (request filed)

UL (Category Control Number NITW)

UL (File No. E336299) Delivery program

Type Wall-mounting housing CSWall-mounting housing with mounting plate Color Light gray (RAL 7035)

Gray Technical data - mechanical

Design type Canted and seam welded, including two M6 threaded bolts for earth conductor connections inside the enclosure. Surface finishing Structured powder spray polyester based paint finish

Gloss

Semi-textured

Powder coating Surface treatment Structured powder spray polyester based paint finish Mounting method 9 mm drilling dimensions for wall mounting (Back plate)

Wall fastening

Intermediate mounting Mounting plate height 370 mm Mounting plate material Sheet steel, hot-galvanized Mounting plate width 550 mm Material Steel

Steel plate Material thickness (body) 1.2 mm Material thickness (bottom plate) 2 mm Material thickness (door) 1.2 mm

Material quality Other Degree of protection IP23 (with ventilati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CS-46/300 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.