

INDUSTRIAL COMPONENT DATA

CS-65/150 111695 Y7-111695 EATON ELECTRIC Wall enclosure, +mounting plate, HxWxD 600x500x150mm

Brand: EATON - MOELLER | Manufacturer Part Number: CS-65/150



Manufacturer	EATON - MOELLER
MPN / Reference	CS-65/150
Catalog number	Y7-111695
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-1481B595FB
Generated	2026-08-05

Product Overview

Wall enclosure, +mounting plate, HxWxD=600x500x150mm

CS-65/150

Eaton xEffect CS LV systems Switch- & Controlgear Enclosure. Wall enclosure with mounting plate, HxWxD=600x500x150mm

Wall-mounting enclosure CS, door with continuous foamed-in polyurethane gasket, shock resistance category IK09 to EN 62262, single door, door hinges right, opening angle 120°, door hinge pins with quick change technology, door profile molding with perforation at 25 mm intervals for fixing DIN mounting rails or for fixing cable conduits and leads, standardized locking system with sash fastener, made completely of metal, with mounting plate sheet steel, equipment supplied: lock, 3mm double ward key. Optional accessory equipment e.g. rotary comfort grip PHZ-A-ADD-ON with cylinder lock PHZ-E10/30-GS. Designed according IEC/EN 62208.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

General specifications

Product Name Eaton xEffect CS enclosure single door Catalog Number 111695 Model Code CS-65/150 EAN

4015081112548 Product Length/Depth 150 mm Product Height 600 mm Product Width 500 mm Product Weight 15.48 kg

Compliances RoHS conform

UL 508A; CSA-C22.2 No.14; IEC/EN 62208; CE marking

UL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the

back sheet metal enclosure) Certifications UL CSA08 (request filed)

UL (Category Control Number NITW)

UL (File No. E336299)

In accordance with Directive 2015/863/EU of the European Parliament and Council

IEC/EN 62208 Catalog Notes Foamed polyurethane sealing throughout. Impact resistance category IK10 to EN 62262.

Sheet steel mounting plate. Bottom plate with foamed gasket. Single door, door stop on the right, door opening angle 120°.

Door hinge pins with quick chang Delivery program

Type Color Gray

Light gray (RAL 7035) Technical data - mechanical

Design type Canted and seam welded, including two M6 threaded bolts for earth conductor connections inside the enclosure. Surface finishing Gloss

Powder coating

Structured powder spray polyester based paint finish

Semi-textured Surface treatment Structured powder spray polyester based paint finish Mounting method Wall fastening

9 mm drilling dimensions for wall mounting (Back plate)

Intermediate mounting Mounting plate height 570 mm Mounting plate material Sheet steel, hot-galvanized Mounting plate width 450 mm Materia...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CS-65/150 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.