

INDUSTRIAL COMPONENT DATA

CS-65/200 111696 Y7-111696 EATON ELECTRIC Wall enclosure, +mounting plate, HxWxD 600x500x200mm

Brand: EATON - MOELLER | Manufacturer Part Number: CS-65/200



Manufacturer	EATON - MOELLER
MPN / Reference	CS-65/200
Catalog number	Y7-111696
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-791E2E5A96
Generated	2026-08-05

Product Overview

Wall enclosure, +mounting plate, HxWxD=600x500x200mm

CS-65/200

Eaton xEffect CS LV systems Switch- & Controlgear Enclosure. Wall enclosure with mounting plate, HxWxD=600x500x200mm

Wall-mounting enclosure CS, door with continuous foamed-in polyurethane gasket, shock resistance category IK09 to EN 62262, single door, door hinges right, opening angle 120°, door hinge pins with quick change technology, door profile molding with perforation at 25 mm intervals for fixing DIN mounting rails or for fixing cable conduits and leads, standardized locking system with sash fastener, made completely of metal, with mounting plate sheet steel, equipment supplied: lock, 3mm double ward key. Optional accessory equipment e.g. rotary comfort grip PHZ-A-ADD-ON with cylinder lock PHZ-E10/30-GS. Designed according IEC/EN 62208.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

General specifications

Product Name Eaton xEffect CS enclosure single door Catalog Number 111696 Model Code CS-65/200 EAN

4015081112555 Product Length/Depth 200 mm Product Height 600 mm Product Width 500 mm Product Weight 16.59 kg

Compliances RoHS conform

UL 508A; CSA-C22.2 No.14; IEC/EN 62208; CE marking

UL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the

back sheet metal enclosure) Certifications IEC/EN 62208

UL (File No. E336299)

UL CSA08 (request filed)

In accordance with Directive 2015/863/EU of the European Parliament and Council

UL (Category Control Number NITW) Catalog Notes Foamed polyurethane sealing throughout. Impact resistance category IK10 to EN 62262. Sheet steel mounting plate. Bottom plate with foamed gasket. Single door, door stop on the right, door opening angle 120°. Door hinge pins with quick change Delivery program

Type Color Light gray (RAL 7035)

Gray Technical data - mechanical

Design type Canted and seam welded, including two M6 threaded bolts for earth conductor connections inside the enclosure. Surface finishing Powder coating

Semi-textured

Structured powder spray polyester based paint finish

Gloss Surface treatment Structured powder spray polyester based paint finish Mounting method 9 mm drilling dimensions for wall mounting (Back plate)

Wall fastening

Intermediate mounting Mounting plate height 570 mm Mounting plate material Sheet steel, hot-galvanized Mounting plate width 450 mm Material...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CS-65/200 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.