

**INDUSTRIAL COMPONENT DATA**

# CS-75/250 111703 Y7-111703 EATON ELECTRIC Wall enclosure, +mounting plate, HxWxD 700x500x250mm

Brand: EATON - MOELLER | Manufacturer Part Number: CS-75/250



|                 |                                      |
|-----------------|--------------------------------------|
| Manufacturer    | EATON - MOELLER                      |
| MPN / Reference | CS-75/250                            |
| Catalog number  | Y7-111703                            |
| Category        | Enclosure/switchgear cabinet (empty) |
| Minimum order   | 1 Pcs                                |
| Document ID     | EO-F5999044EA                        |
| Generated       | 2026-08-05                           |

## Product Overview

Wall enclosure, +mounting plate, HxWxD=700x500x250mm

CS-75/250

Eaton xEffect CS LV systems Switch- & Controlgear Enclosure. Wall enclosure with mounting plate, HxWxD=700x500x250mm

Wall-mounting enclosure CS, door with continuous foamed-in polyurethane gasket, shock resistance category IK09 to EN 62262, single door, door hinges right, opening angle 120°, door hinge pins with quick change technology, door profile molding with perforation at 25 mm intervals for fixing DIN mounting rails or for fixing cable conduits and leads, standardized locking system with sash fastener, made completely of metal, with mounting plate sheet steel, equipment supplied: lock, 3mm double ward key. Optional accessory equipment e.g. rotary comfort grip PHZ-A-ADD-ON with cylinder lock PHZ-E10/30-GS. Designed according IEC/EN 62208.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                              |
|--------------|------------------------------|
| Catalog path | EATON - MOELLER > Enclosures |
|--------------|------------------------------|

## Additional Product Information

General specifications

Product Name Eaton xEffect CS enclosure single door Catalog Number 111703 Model Code CS-75/250 EAN 4015081112623 Product Length/Depth 250 mm Product Height 700 mm Product Width 500 mm Product Weight 23.07 kg Compliances UL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the back sheet metal enclosure) UL 508A; CSA-C22.2 No.14; IEC/EN 62208; CE marking

RoHS conform Certifications UL 508A

IEC Rated

IEC/EN 60529

CSA Std. C22.2 No. 14

UL Listed

In accordance with Directive 2015/863/EU of the European Parliament and Council

UL (Category Control Number NITW)

UL CSA08 (request filed)

UL (File No. E336299)

IEC/EN 62208 Catalog Notes Foamed polyurethane sealing throughout. Impact resistance category IK09 to EN 62262.

Sheet steel mounting plate. Bottom plate with foamed gasket. Single door, door stop on the right, door opening angle 120°.

Door hinge pins with quick chang Delivery program

Type Color Gray

Light gray (RAL 7035) Technical data - mechanical

Design type Canted and seam welded, including two M6 threaded bolts for earth conductor connections inside the enclosure. Surface finishing Gloss

Powder coating

Semi-textured

Structured powder spray polyester based paint finish Surface treatment Structured powder spray polyester based paint finish Mounting method 9 mm drilling dimensions for wall mounting (Back plate)

Wall fastening

Intermediate mounting Mounting plate height 670 mm Mounting plate material....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CS-75/250 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.