

INDUSTRIAL COMPONENT DATA

CS-84/250 111705 Y7-111705 EATON ELECTRIC Wall enclosure, +mounting plate, HxWxD 800x400x250mm

Brand: EATON - MOELLER | Manufacturer Part Number: CS-84/250



Manufacturer	EATON - MOELLER
MPN / Reference	CS-84/250
Catalog number	Y7-111705
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-C2E39C9E45
Generated	2026-08-05

Product Overview

Wall enclosure, +mounting plate, HxWxD=800x400x250mm

CS-84/250

Eaton xEffect CS LV systems Switch- & Controlgear Enclosure. Wall enclosure with mounting plate, HxWxD=800x400x250mm

Wall-mounting enclosure CS, door with continuous foamed-in polyurethane gasket, shock resistance category IK09 to EN 62262, single door, door hinges right, opening angle 120°, door hinge pins with quick change technology, door profile molding with perforation at 25 mm intervals for fixing DIN mounting rails or for fixing cable conduits and leads, standardized locking system with sash fastener, made completely of metal, with mounting plate sheet steel, equipment supplied: lock, 3mm double ward key. Optional accessory equipment e.g. rotary comfort grip PHZ-A-ADD-ON with cylinder lock PHZ-E10/30-GS. Designed according IEC/EN 62208.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect CS enclosure single door Catalog Number 111705 Model Code CS-84/250 EAN

4015081112647 Product Length/Depth 250 mm Product Height 800 mm Product Width 400 mm Product Weight 23.72 kg

Compliances RoHS conform

UL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the back sheet metal enclosure)

UL 508A; CSA-C22.2 No.14; IEC/EN 62208; CE marking Certifications In accordance with Directive 2015/863/EU of the European Parliament and Council
IEC/EN 62208
UL (Category Control Number NITW)
UL CSA08 (request filed)
UL (File No. E336299) Delivery program
Type Wall-mounting housing CSWall-mounting housing with mounting plate Color Light gray (RAL 7035)
Gray Technical data - mechanical
Design type Canted and seam welded, including two M6 threaded bolts for earth conductor connections inside the enclosure. Surface finishing Structured powder spray polyester based paint finish
Powder coating
Gloss
Semi-textured Surface treatment Structured powder spray polyester based paint finish Mounting method Wall fastening
9 mm drilling dimensions for wall mounting (Back plate)
Intermediate mounting Mounting plate height 770 mm Mounting plate material Sheet steel, hot-galvanized Mounting plate width 350 mm Material Steel plate
Steel Material thickness (body) 1.5 mm Material thickness (bottom plate) 2 mm Material thickness (door) 1.5 mm Material quality Other Degree of protection IK09
IP23 (with vent...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CS-84/250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.