

INDUSTRIAL COMPONENT DATA

CS-86/300 111708 Y7-111708 EATON ELECTRIC Wall enclosure, +mounting plate, HxWxD 800x600x300mm

Brand: EATON - MOELLER | Manufacturer Part Number: CS-86/300



Manufacturer	EATON - MOELLER
MPN / Reference	CS-86/300
Catalog number	Y7-111708
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-B76937FEAF
Generated	2026-08-05

Product Overview

Wall enclosure, +mounting plate, HxWxD=800x600x300mm

CS-86/300

Eaton xEffect CS LV systems Switch- & Controlgear Enclosure. Wall enclosure with mounting plate, HxWxD=800x600x300mm

Wall-mounting enclosure CS, door with continuous foamed-in polyurethane gasket, shock resistance category IK09 to EN 62262, single door, door hinges right, opening angle 120°, door hinge pins with quick change technology, door profile molding with perforation at 25 mm intervals for fixing DIN mounting rails or for fixing cable conduits and leads, standardized locking system with sash fastener, made completely of metal, with mounting plate sheet steel, equipment supplied: lock, 3mm double ward key. Optional accessory equipment e.g. rotary comfort grip PHZ-A-ADD-ON with cylinder lock PHZ-E10/30-GS. Designed according IEC/EN 62208.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Enclosures**

Additional Product Information

General specifications

Product Name Eaton xEffect CS enclosure single door Catalog Number 111708 Model Code CS-86/300 EAN 4015081112678 Product Length/Depth 300 mm Product Height 800 mm Product Width 600 mm Product Weight 34.6 kg Compliances UL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the back sheet metal enclosure) RoHS conform

UL 508A; CSA-C22.2 No.14; IEC/EN 62208; CE marking Certifications IEC/EN 62208

In accordance with Directive 2015/863/EU of the European Parliament and Council

UL (Category Control Number NITW)

UL CSA08 (request filed)

UL (File No. E336299) Delivery program

Type Wall-mounting housing CSWall-mounting housing with mounting plate Color Gray

Light gray (RAL 7035) Technical data - mechanical

Design type Canted and seam welded, including two M6 threaded bolts for earth conductor connections inside the enclosure. Surface finishing Semi-textured

Powder coating

Gloss

Structured powder spray polyester based paint finish Surface treatment Structured powder spray polyester based paint finish Mounting method 9 mm drilling dimensions for wall mounting (Back plate)

Wall fastening

Intermediate mounting Mounting plate height 770 mm Mounting plate material Sheet steel, hot-galvanized Mounting plate width 550 mm Material Steel

Steel plate Material thickness (body) 1.5 mm Material thickness (bottom plate) 2 mm Material thickness (door) 1.5 mm

Material quality Other Degree of protection IK09

IP66

12 (NEMA)

I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CS-86/300 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.