

INDUSTRIAL COMPONENT DATA

CS-88/200 111709 Y7-111709 EATON ELECTRIC Wall enclosure, +mounting plate, HxWxD 800x800x200mm

Brand: EATON - MOELLER | Manufacturer Part Number: CS-88/200



Manufacturer	EATON - MOELLER
MPN / Reference	CS-88/200
Catalog number	Y7-111709
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-C10DFF4691
Generated	2026-08-04

Product Overview

Wall enclosure, +mounting plate, HxWxD=800x800x200mm

CS-88/200

Eaton xEffect CS LV systems Switch- & Controlgear Enclosure. Wall enclosure with mounting plate, HxWxD=800x800x200mm

Wall-mounting enclosure CS, door with continuous foamed-in polyurethane gasket, shock resistance category IK09 to EN 62262, single door, door hinges right, opening angle 120°, door hinge pins with quick change technology, door profile molding with perforation at 25 mm intervals for fixing DIN mounting rails or for fixing cable conduits and leads, standardized locking system with sash fastener, made completely of metal, with mounting plate sheet steel, equipment supplied: lock, 3mm double ward key. Optional accessory equipment e.g. rotary comfort grip PHZ-A-ADD-ON with cylinder lock PHZ-E10/30-GS. Designed according IEC/EN 62208.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Enclosures**

Additional Product Information

General specifications

Product Name Eaton xEffect CS enclosure single door Catalog Number 111709 Model Code CS-88/200 EAN 4015081112685 Product Length/Depth 200 mm Product Height 800 mm Product Width 800 mm Product Weight 40.53 kg Compliances UL CSA09 (may be provided with metal sub-panel, no back mounted components are allowed between sub-panel and the back sheet metal enclosure) RoHS conform

UL 508A; CSA-C22.2 No.14; IEC/EN 62208; CE marking Certifications UL (File No. E336299)

UL (Category Control Number NITW)

IEC/EN 62208

In accordance with Directive 2015/863/EU of the European Parliament and Council

UL CSA08 (request filed) Product specifications

Special features Bottom plate enclosed, foamed gasket, can be unscrewed for F3A-... flanges or for assembly by userFoamed polyurethane sealing throughout.Impact resistance category IK09 to EN 62262.Sheet steel mounting plateBottom plate with foamed gasket.Single door, door stop on the right, door opening angle 120°Door hinge pins with quick change technology.Standardized locking system with sash fastener.Powder coating RAL 7035 inside and outsideLock, 3 mm double ward keyIncluding M6 threaded welded studs for earth conductor connections in the doorSide plates without aperturesTop plate without apertures Type Wall-mounting housing CSWall-mounting housing with mounting plate Features Wall build in

Pole fastening 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dis...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CS-88/200 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.