

INDUSTRIAL COMPONENT DATA

BP-F-1000/17/3-F-W 120695 0002460971 EATON ELECTRIC

White floor standing distribution board, flexible surfac..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-1000/17/3-F-W



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-1000/17/3-F-W
Catalog number	0002460971
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-965BA3C7ED
Generated	2026-08-06

Product Overview

White floor standing distribution board, flexible surface mounting, W = 1000 mm, H = 1760 mm, D = 300 mm
Flexible-configuration floor standing distribution board, IP30, white, RAL 9016, width 1000 mm, outside height 1760 mm, front plate height 1650 mm, depth 300 mm, without surface mounting, no gland plate insert, without door, no BPZ-FPS front plate support, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required . indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic empty enclosure Catalog Number 120695 Model Code BP-F-1000/17/3-F-W EAN 4015081185252 Product Length/Depth 315 mm Product Height 1780 mm Product Width 1015 mm Product Weight 43.5 kg

Compliances RoHS conform Delivery program

Type Basic device Application Indoor (installation site) Color Traffic white (RAL 9016)

White Technical data - mechanical

Surface finishing With powder coating

Powder coating Mounting method Floor standing distribution board

Detached Material Steel

Sheet steel Material quality Other Number of connector holes 0 Number of covers/doors 2 Number of locks 0 Permissible load of the door(s) according to IEC 62208 - max 0 N Permissible load of the enclosure according to IEC 62208 - max 0 N Permissible load of the mounting plate according to IEC 62208 - max 0 N Grade material Sheet steel Installation type Floor installation possible Temperature-rise verification as per IEC 60890

Heat diss. ambient 35°C delta T: 20°C free stand middle encl. top (IEC 60890) 216 W Heat diss. ambient 35°C delta T: 20°C wall mount middle encl. top (IEC 60890) 204 W Heat diss. ambient 35°C delta T: 35°C free stand middle encl. top (IEC 60890) 434 W Heat diss. ambient 35°C delta T: 35°C wall mount middle encl. top (IEC 60890) 410 W Heat diss. ambient 35°C delta T: 20°C free stand individ. encl. top (IEC 60890) 227 W Heat diss. ambient 35°C delta T: 20°C free stand starting encl. top (IEC 60890) 221 W Heat diss. ambient 35°C delta T: 20...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-1000/17/3-F-W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.