

INDUSTRIAL COMPONENT DATA

BP-F-1200/17/3-F-W 120697 0002460973 EATON ELECTRIC

White floor standing distribution board, flexible surfac..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-1200/17/3-F-W



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-1200/17/3-F-W
Catalog number	0002460973
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-3C5CC64F09
Generated	2026-08-06

Product Overview

White floor standing distribution board, flexible surface mounting, W = 1200 mm, H = 1760 mm, D = 300 mm
Flexible-configuration floor standing distribution board, IP30, white, RAL 9016, width 1200 mm, outside height 1760 mm, front plate height 1650 mm, depth 300 mm, without surface mounting, no gland plate insert, without door, no BPZ-FPS front plate support, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required . indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

White floor standing distribution board, flexible surface mounting, W = 1200 mm, H = 1760 mm, D = 300 mm EL-Nummer (Norway) 0002460973 Flexible-configuration floor standing distribution board, IP30, white, RAL 9016, width 1200 mm, outside height 1760 mm, front plate height 1650 mm, depth 300 mm, without surface mounting, no gland plate insert, without door, no BPZ-FPS front plate support, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required. indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior

fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door [Delivery program

Mounting type Floor standing distribution board Material Sheet steel Installation site Indoor Degree of Protection IP30

Surface finish With powder coating Width 1200 mm Depth 300 mm Height 1760 mm Colour white (RAL 9016) , Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-1200/17/3-F-W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.