

INDUSTRIAL COMPONENT DATA

BP-F-1000/17/3-P-W 102381 0002459209 EATON ELECTRIC
White floor standing distribution board with locking rot..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-1000/17/3-P-W



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-1000/17/3-P-W
Catalog number	0002459209
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-668979E9CF
Generated	2026-08-06

Product Overview

White floor standing distribution board with locking rotary lever, W = 1000 mm, H = 1760 mm, D = 300 mm
Floor standing distribution board with locking rotary lever, IP30, white, RAL 9016, width 1000 mm, outside height 1760 mm, front plate height 1650 mm, depth of 300 mm, incl. gland plate inserts at the top and bottom, metal door with rotary lever, door can be right-hand or left-hand door, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required. indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

White floor standing distribution board with locking rotary lever, W = 1000 mm, H = 1760 mm, D = 300 mm EL-Nummer (Norway) 0002459209 Floor standing distribution board with locking rotary lever, IP30, white, RAL 9016, width 1000 mm, outside height 1760 mm, front plate height 1650 mm, depth of 300 mm, incl. gland plate inserts at the top and bottom, metal door with rotary lever, door can be right-hand or left-hand door, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required. indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring

area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure [Delivery program

Mounting type Floor standing distribution board Material Sheet steel Door interlock Rotary lever Installation site Indoor Degree of Protection IP30 Surface finish With powder coating Width 1000 mm Depth 300 mm Height 1760 mm Colour white (RAL 9016) , Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Indiv...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-1000/17/3-P-W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.