


INDUSTRIAL COMPONENT DATA

BP-F-800/20/3-W 102340 0002459188 EATON ELECTRIC White floor standing distribution board with three-point tu..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-F-800/20/3-W



Manufacturer	EATON - MOELLER
MPN / Reference	BP-F-800/20/3-W
Catalog number	0002459188
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-15E1876A1F
Generated	2026-08-06

Product Overview

White floor standing distribution board with three-point turn-lock, W = 800 mm, H = 2060 mm, D = 300 mm
Floor standing distribution board with cam lock, IP30, white, RAL 9016, width 800 mm, outside height 2060 mm, front plate height 1950 mm, depth of 300 mm, incl. gland plate inserts at the top and bottom, metal door with cam lock, door can be right-hand or left-hand door, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required . indoor installation with MSW or mounting towers possible, earthed metal covers, extraordinary stability as a result of welded construction, ample wiring area, variable interior fittings with / without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Fuse-link, LV, 800 A, AC 600 V, 44 x 110 mm, T, UL, very fast acting Fuse, fuse-link, low voltage, 800 A, AC 600 V, 44 x 110 mm, Class T, UL, very fast acting, commonly applied in electric heat circuits, load center, disconnect switches, and meters [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 800 A Rated voltage AC 600 V Size 44 x 110 mm Utilization category T usable for size/applications commonly applied in electric heat circuits, load center, disconnect switches, and meters Release characteristic [class] very fast acting Standard/Approval UL , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size Other Rated current 800 A Rated voltage 600 V Voltage type AC Rated switching capacity 200 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No] ETIM for 102340 Cabinets and enclosures (EC000261)

Feature Name

Feature Value

Width (EF000008)

815 mm

Height (EF000040)

2080 mm

Depth (EF000049)

315 mm

Material (EF002169)

Steel

Material quality (EF001257)

Other

Surface finishing (EF006569)

Powder coated

Colour (EF000007)

White

RAL-number (EF000116)

9016

Freestanding (EF020363)

Yes

Floor standing wall model (EF015208)

No

Suitable for wall m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-F-800/20/3-W with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.