

INDUSTRIAL COMPONENT DATA

+NZM4-4-XAVE 266718 Y7-266718 EATON ELECTRIC

Withdrawable carrier, 4p, 1600A. Can only be sold assembled.

Brand: EATON - MOELLER | Manufacturer Part Number: +NZM4-4-XAVE



Manufacturer	EATON - MOELLER
MPN / Reference	+NZM4-4-XAVE
Catalog number	Y7-266718
Category	Chassis part power circuit breaker
Minimum order	1 Pcs
Document ID	EO-56A3F1BF8C
Generated	2026-08-05

Product Overview

Withdrawable carrier, 4p, 1600A. Can only be sold assembled.

+NZM4-4-XAVE

Withdrawable carrier, 4p, 1600A

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: for NZM circuit-breakers and N switch-disconnectors not UL/CSA approved. Can be used for: NZM4, N4, NZM4-4, N4-4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

Withdrawable carrier, 4p, 1600AOptional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups.

Notes: for NZM circuit-breakers and N switch-disconnectors not UL/CSA approved. Can be used for: NZM4, N4, NZM4-4, N4-4

General specificationsProduct nameEaton Moeller series NZM plug-in unitPart

no.+NZM4-4-XAVEEAN4015082667184Product Length/Depth509 millimetreProduct height240 millimetreProduct width367 millimetreProduct weight12.6 kilogramCompliancesIEC

RoHS conformCertificationsIEC/EN 60947Product TradenameNZMProduct TypeAccessoriesProduct Sub TypePlug-in unitDelivery programTypeAccessory

Extension insert for basic unitNumber of polesFour-poleNominal current1488 AFeaturesVersion as built-in deviceSpecial

featuresExtension insert is assembled with basic switch in the factory to form extension technology
switchFrameNZM4Technical Data - ElectricalElectrical connection type of main circuitOtherIsolation300 V AC (between the
auxiliary contacts)
500 V AC (between auxiliary contacts and main contacts)Direction of incoming supplyAs requiredTechnical Data -
MechanicalMounting MethodWithdrawableMounting positionVerticalProtection against direct contactFinger and
back-of-hand proof to VDE 0106 part 100Shock resistance15 g (half-sinusoidal shock 11 ms)Climatic proofingDamp heat,
constant, to IEC 60068-2-78
Damp heat, cyclic, to IEC 60068-2-30Spe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +NZM4-4-XAVE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.