

INDUSTRIAL COMPONENT DATA

XC-303-C11-000 191082 Y7-191082 EATON ELECTRIC XC303 modular PLC, small PLC, programmable CODESYS 3, SD Slot..

Brand: EATON - MOELLER | Manufacturer Part Number: XC-303-C11-000



Manufacturer	EATON - MOELLER
MPN / Reference	XC-303-C11-000
Catalog number	Y7-191082
Category	PLC CPU-module
Minimum order	1 Pcs
Document ID	EO-B4C61B4633
Generated	2026-08-03

Product Overview

XC303 modular PLC, small PLC, programmable CODESYS 3, SD Slot, Ethernet, CAN
XC-303-C11-000

With the XC-303, Eaton offers a high-performance and flexible control system that makes it possible for machinery and equipment manufacturers to achieve a streamlined and modern automation concept in combination with the compact XN300 I/O system and the innovative XV300 multi-touch panel. Ethernet interfaces for connection to different networks paired with standard CAN and RS485 interfaces expand the functions of the XC-303 into a universal data and communication point for networked equipment. The communicative compact controller is CODESYS 3 programmable, supports WEB visualization in HTML5 format and the OPC-UA server ensures data exchange in machine-to-machine (M2M) communication. Up to 32 modules of the XN300 I/O system allow for connection as local I/O levels. The following interfaces are included in this version: microSD, Ethernet and CAN.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Remote I / O Modules XN300
--------------	--

Additional Product Information

General specifications

Product Name Eaton XC Modular PLC Catalog Number 191082 Model Code XC-303-C11-000 EAN 4015081915682
Product Length/Depth 108 mm Product Height 65 mm Product Width 85 mm Product Weight 0.28 kg Certifications CE
EN 61131

UL listed

EAC

UL File No.: E205091

cULus Listed Catalog Notes Protective devices must be installed directly at the inductive load in order to prevent interference. Features & Functions

Features Short-circuit protection (digital outputs) Functions Redundancy

Additional program memory possible General

Connection type Push-in spring-cage terminal, Connection design in TOP direction Degree of protection IP20 Memory capacity 512,000 kByte Model Modular Mounting method Rail mounting possible Overvoltage category II Pollution degree 2 Protocol MODBUS

CAN

Other bus systems

TCP/IP

EtherNet/IP Rated operational voltage 24 V

160 V (terminations) Voltage type DC Ambient conditions, mechanical

Height of fall (IEC/EN 60068-2-32) - max 1 m Mounting position Vertical (on horizontal top-hat rail) Shock resistance 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts Vibration resistance 5 - 8.4 / 8.4 -150 Hz, 3,5 mm / 1 g Climatic environmental conditions

Air pressure 795 - 1080 hPa (operation) Ambient operating temperature - min -20 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 80 °C Climatic proofing Damp heat, constant, to IEC 60068-2-3

Dry hea...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XC-303-C11-000 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.