

INDUSTRIAL COMPONENT DATA

XN-P4T-SBBC 140076 Y7-140076 EATON ELECTRIC Base module washer XI/ON, for feeder unit, tension spring, 4 con..

Brand: EATON - MOELLER | Manufacturer Part Number: XN-P4T-SBBC



Manufacturer	EATON - MOELLER
MPN / Reference	XN-P4T-SBBC
Catalog number	Y7-140076
Category	Fieldbus, decentr. periphery - mounting frame
Minimum order	1 Pcs
Document ID	EO-36751EE7F9
Generated	2026-08-05

Product Overview

Base module washer XI/ON, for feeder unit, tension spring, 4 connection levels

XN-P4T-SBBC

Rack, XI/ON slice card base modules, Connection levels: 4 connection levels, Connection technique: Spring-loaded terminals, for Slice module, Base modules for field power supply, Base module for the gateway supply (with XN-BR-24VDC-D), Degree of Protection: IP20, For use with: XN-BR-24VDC-D, XN-PF-24VDC-D, XN-PF-120/230VAC-D, Standards: EN 61000-6-2, EN 61000-6-4, EN 61131-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Remote I / O Modules XION
--------------	---

Additional Product Information

General specifications

Product Name Eaton XN Rack Catalog Number 140076 Model Code XN-P4T-SBBC EAN 7640130120990 Product Length/Depth 128.9 mm Product Height 49.9 mm Product Width 12.6 mm Product Weight 0.035 kg Compliances RoHS Compliant

CE Marked Certifications UL Listed

IEC/EN 61000-6-2

Rated data for terminations according to IEC/EN 60947-7-1

UL Category Control No.: NRAQ, NRAQ7

IEC/EN 6113-2

CE

UL File No.: E205091

CSA-C22.2 No. 142

CE, cUL

UL Recognized

UL 508

Certified by UL for use in Canada

IEC/EN 61131-2

CSA Class No.: 2252-01, 2252-81

UL report applies to both US and Canada

IEC/EN 61000-6-4 Catalog Notes Base module for the gateway supply (with XN-BR-24V DC-D) Features & Functions

Color Gray Fitted with: Pluggable modules, central modules

Pluggable modules, others

Power supply General

Degree of protection IP20 Mounting method Rail mounting possible Number of connection levels 4 Type XI/ON slice card
base module Used with XN-PF-120/230VAC-D

XN-BR-24VDC-D

XN-PF-24VDC-D Voltage type DC Ambient conditions, mechanical

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Continuous
according to IEC/EN 60068-2-29

Mechanical, According to IEC/EN 60068-2-27 Vibration resistance According to IEC/EN 60068-2-6 Climatic environmental
conditions

Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Environmental conditions Harmful
gasses - SO2: 10 ppm (relative humidity < 75%, no condensation)

Harmful g...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-P4T-SBBC with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.