

INDUSTRIAL COMPONENT DATA

XN-S3T-SBC 140079 Y7-140079 EATON ELECTRIC Base module washer XI/ON, tension spring, 3 connection levels, CO..

Brand: EATON - MOELLER | Manufacturer Part Number: XN-S3T-SBC



Manufacturer	EATON - MOELLER
MPN / Reference	XN-S3T-SBC
Catalog number	Y7-140079
Category	Fieldbus, decentr. periphery - mounting frame
Minimum order	1 Pcs
Document ID	EO-2B0F43AF18
Generated	2026-08-05

Product Overview

Base module washer XI/ON, tension spring, 3 connection levels, con. to C rail

XN-S3T-SBC

Rack, XI/ON slice card base modules, Connection levels: 3 connection levels, Connection technique: Spring-loaded terminals, for Slice module, Connection to C rail, Degree of Protection: IP20, For use with: XN-2DO-24VDC-0.5A-P, XN-2DO-24VDC-0.5A-N, XN-2DO-24VDC-2A-P, XN-2DO-120/230VAC-0.5A, Standards: EN 61000-6-2, EN 61000-6-4, EN 61131-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Remote I / O Modules XION

Additional Product Information

General specifications

Product Name Eaton XN Rack Catalog Number 140079 Model Code XN-S3T-SBC EAN 7640130121164 Product Length/Depth 117.6 mm Product Height 49.9 mm Product Width 12.6 mm Product Weight 0.031 kg Certifications UL Recognized

Certified by UL for use in Canada

Rated data for terminations according to IEC/EN 60947-7-1

IEC/EN 6113-2

CE

UL Category Control No.: NRAQ, NRAQ7

IEC/EN 61000-6-2

IEC/EN 61000-6-4

CSA-C22.2 No. 142

IEC/EN 61131-2

UL 508

UL report applies to both US and Canada

CSA Class No.: 2252-01, 2252-81

UL File No.: E205091

CE, cUL Features & Functions

Fitted with: Pluggable modules, digital I/O

Power supply

Pluggable modules, central modules General

Degree of protection IP20 Mounting method Rail mounting possible Number of connection levels 3 Type XI/ON slice card base module Used with XN-2DO-120/230VAC-0.5A

XN-2DO-24VDC-0.5A-P

XN-2DO-24VDC-2A-P

XN-2DO-24VDC-0.5A-N Voltage type DC Ambient conditions, mechanical

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Mechanical, According to IEC/EN 60068-2-27

Continuous according to IEC/EN 60068-2-29 Vibration resistance According to IEC/EN 60068-2-6 Climatic environmental conditions

Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Environmental conditions Harmful gasses - H2S: 1 ppm (relative humidity < 75%, no condensation)

Harmful gasses - SO2: 10 ppm (relative humidity < 75%, no condensation) Relative humidity 5 - 95 % (i...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-S3T-SBC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.