

INDUSTRIAL COMPONENT DATA

XN-S4T-SBBS-CJ 140084 Y7-140084 EATON ELECTRIC Base module washer XI/ON, tension spring, 4 connection levels..

Brand: EATON - MOELLER | Manufacturer Part Number: XN-S4T-SBBS-CJ



Manufacturer	EATON - MOELLER
MPN / Reference	XN-S4T-SBBS-CJ
Catalog number	Y7-140084
Category	Fieldbus, decentr. periphery - mounting frame
Minimum order	1 Pcs
Document ID	EO-30CC6D1CD4
Generated	2026-08-03

Product Overview

Base module washer XI/ON, tension spring, 4 connection levels, with temperature compensation

XN-S4T-SBBS-CJ

Rack, XI/ON slice card base modules, Connection levels: 4 connection levels, Connection technique: Spring-loaded terminals, for Slice module, Base module with temperature sensors for cold-junction compensation, Degree of Protection: IP20, For use with: XN-2AI-THERMO-PI, Standards: EN 61000-6-2, EN 61000-6-4, EN 61131-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Remote I / O Modules XION

Additional Product Information

General specifications

Product Name Eaton XN Rack Catalog Number 140084 Model Code XN-S4T-SBBS-CJ EAN 7640130121232 Product Length/Depth 128.9 mm Product Height 49.9 mm Product Width 12.6 mm Product Weight 0.038 kg Certifications UL 508

UL Recognized

IEC/EN 6113-2

UL report applies to both US and Canada

CE, cUL

Certified by UL for use in Canada

IEC/EN 61131-2

UL Category Control No.: NRAQ, NRAQ7

CE

Rated data for terminations according to IEC/EN 60947-7-1

CSA-C22.2 No. 142

IEC/EN 61000-6-2

UL File No.: E205091

CSA Class No.: 2252-01, 2252-81

IEC/EN 61000-6-4 Features & Functions

Fitted with: Pluggable modules, central modules

Pluggable modules, analog I/O

Power supply

With temperature sensors for cold-junction compensation General

Degree of protection IP20 Mounting method Rail mounting possible Number of connection levels 4 Type XI/ON slice card base module Used with XN-2AI-THERMO-PI Voltage type DC Ambient conditions, mechanical

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Mechanical, According to IEC/EN 60068-2-27

Continuous according to IEC/EN 60068-2-29 Vibration resistance According to IEC/EN 60068-2-6 Climatic environmental conditions

Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Environmental conditions Harmful gasses - SO₂: 10 ppm (relative humidity < 75%, no condensation)

Harmful gasses - H₂S: 1 ppm (relative humidity < 75%, no condensation) Relative humidity 5 - 95 % (indoor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-S4T-SBBS-CJ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.