

INDUSTRIAL COMPONENT DATA

XN-322-4AIO-I 183182 Y7-183182 EATON ELECTRIC Analog I/O module, 2 analog inputs and 2 analog outputs, 0/4 t..

Brand: EATON - MOELLER | Manufacturer Part Number: XN-322-4AIO-I



Manufacturer	EATON - MOELLER
MPN / Reference	XN-322-4AIO-I
Catalog number	Y7-183182
Category	Fieldbus, decentr. periphery - analogue I/O module
Minimum order	1 Pcs
Document ID	EO-BF1919FB4B
Generated	2026-08-06

Product Overview

Analog I/O module, 2 analog inputs and 2 analog outputs, 0/4 to 20 mA

XN-322-4AIO-I

Analog mixed module with 2 analog outputs 0/4 to 20 mA (12 bit) and 2 analog inputs 0/4 to 20 mA (16 bit)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Remote I / O Modules XN300
--------------	--

Additional Product Information

General specifications

Product Name Eaton XN-322 I/O module Catalog Number 183182 Model Code XN-322-4AIO-I EAN 4015081781157

Product Length/Depth 104.2 mm Product Height 16.8 mm Product Width 80.3 mm Product Weight 0.055 kg Certifications IEC/EN 61131-2

CULus

IEC/EN 61000-6-2

UL File No.: E135462

IEC/EN 61000-6-4

CE Catalog Notes The max. heat dissipation is specified as the maximum power produced inside the device's housing.

Features & Functions

Current measurement 50 ? typ., input resistance

0 - 20 mA Electric connection type Plug-in connection Features Input, current

Analog outputs configurable

Output, current

Analog inputs configurable

Fieldbus connection over separate bus coupler possible

Input signal, configurable Fitted with: 1 kHz, third-order low-pass input filter

Parameterizable Software input filter Value representation SIGNED16, Current measurement General

Current consumption 55 mA (typ.), for +5 V power supply (internal), Power supply - Input

None mA (typ.), for +24 V, Power supply - Input Degree of protection IP20

NEMA 1 Limit frequency 1 kHz (third-order low-pass filter) Mounting method Rail mounting possible Number of channels 2,

Analog Inputs Overvoltage category III Pollution degree 3 Product category XN-322 analog input and output module

Resolution Type Analog mixed module with 2 analog outputs 0/4 to 20 mA (12 bit) and 2 analog inputs 0/4 to 20 mA (16 bit).

XN300 I/O slice module

Used with XN300

XN-312-... Voltage type DC Ambient conditions, mechanical

Heig...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-322-4AIO-I with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.