

INDUSTRIAL COMPONENT DATA

XN-P3T-SBB-B 140073 Y7-140073 EATON ELECTRIC Block bases XI/ON To refresh the BUS pressure Connection 3 leve..

Brand: EATON - MOELLER | Manufacturer Part Number: XN-P3T-SBB-B



Manufacturer	EATON - MOELLER
MPN / Reference	XN-P3T-SBB-B
Catalog number	Y7-140073
Category	Fieldbus, decentr. periphery - mounting frame
Minimum order	1 Pcs
Document ID	EO-1839761527
Generated	2026-08-06

Product Overview

Block bases XI/ON; To refresh the BUS; pressure Connection; 3 levels of connection

XN-P3T-SBB-B

Eaton XN Base module washer XI/ON, for bus refreshing, tension spring, 3 connection levels

Rack, XI/ON slice card base modules, Connection levels: 3 connection levels, Connection technique: Spring-loaded terminals, for Slice module, Base module for bus refreshing within the station, Degree of Protection: IP20, For use with: XN-BR-24VDC-D, Standards: EN 61000-6-2, EN 61000-6-4, EN 61131-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Remote I / O Modules XION
--------------	---

Additional Product Information

General specifications

Product Name Eaton XN Rack Catalog Number 140073 Model Code XN-P3T-SBB-B EAN 7640130120969 Product Length/Depth 117.6 mm Product Height 49.9 mm Product Width 12.6 mm Product Weight 0.031 kg Certifications UL 508 UL File No.: E205091

UL Category Control No.: NRAQ, NRAQ7

IEC/EN 6113-2

CSA-C22.2 No. 142

CE, cUL

CE

IEC/EN 61131-2

IEC/EN 61000-6-4

Rated data for terminations according to IEC/EN 60947-7-1

UL Recognized

UL report applies to both US and Canada

IEC/EN 61000-6-2

CSA Class No.: 2252-01, 2252-81

Certified by UL for use in Canada Features & Functions

Fitted with: Power supply

Pluggable modules, others

Pluggable modules, central modules General

Degree of protection IP20 Mounting method Rail mounting possible Number of connection levels 3 Type XI/ON slice card base module Used with XN-BR-24VDC-D Voltage type DC Ambient conditions, mechanical

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Mechanical, According to IEC/EN 60068-2-27

Continuous according to IEC/EN 60068-2-29 Vibration resistance According to IEC/EN 60068-2-6 Climatic environmental conditions

Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Environmental conditions Harmful gasses - H2S: 1 ppm (relative humidity < 75%, no condensation)

Harmful gasses - SO2: 10 ppm (relative humidity < 75%, no condensation) Relative humidity 5 - 95 % (indoor, Level RH-2, non-condensing for storage at 45°C) Electro magneti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-P3T-SBB-B with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.