

INDUSTRIAL COMPONENT DATA

XNH2-A400-BT 183058 Y7-183058 EATON ELECTRIC NH fuse-switch 3p box terminal 95 300 mm² mounting plate NH2

Brand: EATON - MOELLER | Manufacturer Part Number: XNH2-A400-BT



Manufacturer	EATON - MOELLER
MPN / Reference	XNH2-A400-BT
Catalog number	Y7-183058
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-7F723ABEBB
Generated	2026-08-04

Product Overview

NH fuse-switch 3p box terminal 95 - 300 mm²; mounting plate; NH2

XNH2-A400-BT

NH fuse switch-disconnector 3 pole with box terminal 95 - 300 mm²; mounting plate; for NH2 fuse-links; optionally lockable with XNH-XLOCK and padlock

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Industrial Fuse Bases
--------------	---

Additional Product Information

NH fuse-switch 3p box terminal 95 - 300 mm²; mounting plate; NH2NH fuse switch-disconnector 3 pole with box terminal 95 - 300 mm²; mounting plate; for NH2 fuse-links; optionally lockable with XNH-XLOCK and padlock

General specificationsProduct nameEaton xEffect XNH device for mounting platePart

no.XNH2-A400-BTEAN4015081779857Product Length/Depth306 millimetreProduct height134 millimetreProduct width210 millimetreProduct weight3.632 kilogramCompliancesRoHS conformCertificationsIEC/EN 60947-3Product

TradenamexEEffectProduct TypeXNH device for mounting plateProduct Sub TypeNoneDelivery programTypeBasic

deviceColorGrayNumber of polesThree-poleActuator typeCover gripTechnical Data - ElectricalVoltage testYes, sliding inspection windowsVoltage rating at AC400 V (AC-23B)

500 V (AC-22B)

690 V (AC-21B)Voltage rating at DC400 V (AC-23B)

500 V (AC-22B)

690 V (AC-21B)Rated operating voltage (Ue) at AC - max690 VRated insulation voltage (Ui)800 V ACRated impulse

withstand voltage (Uimp)8 kVRated uninterrupted current (Iu)400 ARated conditional short-circuit current (Iq)120 kARated operation current (Ie)400 ARated operational current400 A (AC-23B)
400 A (AC-22B)
400 A (AC-21B)
400 A (DC-22B)Rated short-time withstand current (Icw)3 kARated conditional short-circuit rating100 kA (690 V)
120 kA (500 V)Conditioned rated short-circuit current Iq120 kAFrequency rating40 Hz - 60 HzFrequency rating of contacts40 Hz - 60 HzCreepage resistanceCTI 600Power rating at AC-23, 400 V0 kWRated operation p...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XNH2-A400-BT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.