

INDUSTRIAL COMPONENT DATA

XNH2-S400 183065 Y7-183065 EATON ELECTRIC NH fuse-switch 3p flange connection M10 max. 240 mm² busbar 60 mm ..

Brand: EATON - MOELLER | Manufacturer Part Number: XNH2-S400



Manufacturer	EATON - MOELLER
MPN / Reference	XNH2-S400
Catalog number	Y7-183065
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5DEC276884
Generated	2026-08-04

Product Overview

NH fuse-switch 3p flange connection M10 max. 240 mm²; busbar 60 mm; NH2

XNH2-S400

Eaton xEffect - XNH circuit protection. NH fuse-switch 3p flange connection M10 max. 240 mm², busbar 60 mm, NH2 NH fuse switch-disconnector 3 pole with M10 flat terminal max. 240 mm²; busbar 60 mm; for NH2 fuse-links; optionally lockable with XNH-XLOCK and padlock; upper/lower cable connection can be changed in seconds.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Industrial Fuse Bases

Additional Product Information

General specifications

Product Name Eaton xEffect XNH device for busbar system Catalog Number 183065 Model Code XNH2-S400 EAN 4015081779925 Product Length/Depth 306 mm Product Height 160 mm Product Width 210 mm Product Weight 3.329 kg Compliances RoHS conform Certifications IEC/EN 60947-3 Product specifications

Type Basic device Special features Features Halogen free

Standard sealable 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements,

provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XNH2-S400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.