

INDUSTRIAL COMPONENT DATA

XNH3-A630 183071 Y7-183071 EATON ELECTRIC NH fuse-switch 3p flange connection M10 max. 300 mm² mounting plat..

Brand: EATON - MOELLER | Manufacturer Part Number: XNH3-A630



Manufacturer	EATON - MOELLER
MPN / Reference	XNH3-A630
Catalog number	Y7-183071
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-011978EB72
Generated	2026-08-06

Product Overview

NH fuse-switch 3p flange connection M10 max. 300 mm²; mounting plate; NH3 XNH3-A630

Eaton xEffect - XNH circuit protection. NH fuse-switch 3p flange connection M10 max. 300 mm², mounting plate, NH3 NH fuse switch-disconnector 3 pole with M10 flat terminal max. 300 mm²; mounting plate; for NH3 fuse-links; optionally lockable with XNH-XLOCK and padlock

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Industrial Fuse Bases

Additional Product Information

General specifications

Product Name Eaton xEffect XNH device for mounting plate Catalog Number 183071 Model Code XNH3-A630 EAN 4015081779987 Product Length/Depth 306 mm Product Height 143 mm Product Width 250 mm Product Weight 3.674 kg

Compliances RoHS conform Certifications IEC/EN 60947-3 Product specifications

Type Basic device Special features Features Standard sealable

Halogen free 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements,

provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to b...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XNH3-A630 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.