

INDUSTRIAL COMPONENT DATA

XPFMM06-1 109253 EATON ELECTRIC Partition, F, switchgear area/switchgear area, A 600mm

Brand: EATON - MOELLER | Manufacturer Part Number: XPFMM06-1



Manufacturer	EATON - MOELLER
MPN / Reference	XPFMM06-1
Catalog number	109253
Category	Divider panel (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-0C520C0DE7
Generated	2026-08-04

Product Overview

Partition, F, switchgear area/switchgear area, A=600mm

Partition for interior partitioning, for Dubai only, shape 4, section width of 600 mm, partition for use between component mounting area and another component mounting area, without ventilation, sheet steel

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Enclosures**

Additional Product Information

Fuse-link, low voltage, 1.5 A, AC 600 V, 10 x 38 mm, supplemental, UL, CSA, fast-acting Fuse, Fuse-link, low voltage, 1.5 A, AC 600 V, 10 x 38 mm, supplemental, UL, CSA, fast-acting, cylindrical, colour-coded, black, control circuits, lighting circuits, meter circuits, UL 248-14, Breaking Capacity 100 kA, melamine tube [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 1.5 A Rated voltage AC 600 V

Size 10 x 38 mm Utilization category supplemental Description colour-coded

black Breaking Capacity 100 kA usable for size/applications control circuits, lighting circuits, meter circuits Release characteristic [class] fast-acting Standard/Approval UL

CSA Shape cylindrical Material melamine tube Standards/Regulations UL 248-14 , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) ()

[AFZ797013]) Size 10x38 mm Rated voltage 600 - 600 V Rated voltage Other Voltage type AC Utilization category Other Rated operating frequency 45 - 62 Hz Nominal current 1.5 A With striker No Release characteristic Other Breaking capacity 100 kA]

ETIM for 109253 Cabinets and enclosures (EC002525)

Feature Name

Feature Value

Width (EF000008)

520 mm

Height (EF000040)

25 mm

With cable entry (EF000325)

No

With lock (EF006306)

No

For internal se...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XPFMM06-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.