

INDUSTRIAL COMPONENT DATA

XS100 EATON ELECTRIC Air fuse-link, medium voltage, 10 A, AC 36 kV, 50.8 x 565mm, back-up, BS, with striker,..

Brand: EATON - MOELLER | Manufacturer Part Number: XS100



Manufacturer	EATON - MOELLER
MPN / Reference	XS100
Catalog number	10000
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-F65B7EF413
Generated	2026-08-06

Product Overview

100Amp 440Vac OFFSET BLADE TAG BS88 FUSE

Fuse-link, LV, 100 A, AC 440 V, BS88/F3, 27 x 80 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 100 A, AC 440 V, BS88/F3, 27 x 80 mm, gL/gG, BS, offset bladed tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number XS100 EAN 5027590515276

Product Length/Depth 80 mm Product Height 27 mm Product Width 27 mm Product Weight 66.4 g Compliances CE Marked

RoHS Compliant Certifications BS88

IEC 60269

EAC Product specifications

Type Fuse Application general industrial applications Amperage Rating 100 A Fitted with: Offset bladed tags Current type

AC Breaking capacity 80 kA Rated switching capacity 80 kA Rated voltage AC 440 V Class Class gG/gL Fuse type XS

Utilization category gL/gG (cable protection/equipment protection) Color None Interrupt rating 80 kAIC Fuse indicator None

Insulated metal gripping lugs (IMGL) No Connection Blade end Construction BS88/F3 Construction size F3 Fuse shape

Offset bladed tags Voltage type AC Suitable for SC125 Safeclip fuse holder Voltage rating 440 V Fuse system (according to IEC 60269) Fuse system E

ETIM for XS100 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Fuse system E
Fuse construction type according to IEC 60269 (EF015865)
F3
Type of current (EF000143)
AC
Rated voltage AC (EF007682)
440 V
Rated current (EF000227)
100 A
Utilization category according to IEC 60269 (EF002572)
gG (cable protection/equipment protection)
Breaking capacity (EF005617)
80 kA
Colour code (EF000931)
None
Type of fuse status indicator (EF004473)
None

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XS100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.