

INDUSTRIAL COMPONENT DATA

XS25 EATON ELECTRIC Fuse-link, LV, 200 A, AC 400 V, NH02, gFF, IEC, dual indicator, insulated gripping lugs

Brand: EATON - MOELLER | Manufacturer Part Number: XS25



Manufacturer	EATON - MOELLER
MPN / Reference	XS25
Catalog number	10000
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-B204F3CB56
Generated	2026-08-06

Product Overview

25Amp 440V ac OFFSET BLADE TAG BS88 FUSE

25Amp 440V ac OFFSET BLADE TAG BS88 FUSE - Fuse-link, low voltage, 25 A, AC 440 V, 80 kA, BS88/F3, 27 x 80 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 25 A, AC 440 V, BS88/F3, 27 x 80 mm, gL/gG, BS, offset bladed tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 25 A, AC 440 V, 80 kA, BS88/F3, 27 x 80 mm, gL/gG, BSFuse, Fuse-link, low voltage, 25 A, AC 440 V, BS88/F3, 27 x 80 mm, gL/gG, BS, offset bladed tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kADelivery program

Product rangeFuseBasic functionFuse-linkField of applicationlow voltageRated current [I]25 ARated voltageAC 440 VConstruction sizeBS88/F3Size27 x 80 mmUtilization categorygL/gGBreaking Capacity80 kAusable for size/applicationsgeneral industrial applicationsStandard/ApprovalBSShapeoffset bladed tagsStandards/RegulationsBS88-2 IEC 60269-2Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse () [AFZ800015])Construction sizeOtherRated current25 ARated voltage440 VVoltage typeACRated switching capacity80 kAUtilization categorygL/gG (cable protection/equipment protection)Type of fuse status indicatorNoneInsulated metal

gripping lugs (IMGL)No

ETIM for XS25 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

F3

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

440 V

Rated current (EF000227)

25 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protectio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XS25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.