

INDUSTRIAL COMPONENT DATA

XSDMV-240808-BF-2-PI 192615 Y7-192615 EATON ELECTRIC Miniature circuit breaker (MCB), 20A, 1p, C-Char, AC

Brand: EATON - MOELLER | Manufacturer Part Number: XSDMV-240808-BF-2-PI



Manufacturer	EATON - MOELLER
MPN / Reference	XSDMV-240808-BF-2-PI
Catalog number	Y7-192615
Category	Door/operating panel (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-2EC50448B8
Generated	2026-08-06

Product Overview

Miniature circuit breaker (MCB), 20A, 1p, C-Char, AC

XSDMV-240808-BF-2-PI

Door for 2xNZM2 Plug In, safe up to IP31, foam gasket, interlock with 3-mm double-bit key, powder-spray painted, width 800 mm, RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

Delivery program Basic function Miniature circuit-breakers

Number of poles 1 pole

Tripping characteristic C

Application Switchgear for industrial and advanced commercial applications

Rated current In A 20

Rated switching capacity acc. to IEC/EN 60947-2 Icu kA 25

Product range FAZ-T

Technical data Electrical

Standards IEC/EN 60947-2

Rated voltage according to IEC/EN 60947-2 Un V AC 240

Rated switching capacity acc. to IEC/EN 60947-2 Icu kA 25

Rated service short-circuit breaking capacity according to IEC/EN 60947-2 Ics 12,5 kA

Max operational voltage according to IEC/EN 60947-2 V AC 254
Rated switching capacity according to IEC/EN 60947-2 (max operational voltage) Icu kA 15
Rated service short-circuit breaking capacity according to IEC/EN 60947-2 (max operational voltage) Ics 7,5 kA
Max operational voltage DC according to IEC/EN 60947-2 V DC 60/pole
Rated voltage according to IEC/EN 60898-1 Un V AC 240
Rated switching capacity according to IEC/EN 60898-1 Icn kA 15
Rated service short-circuit breaking capacity according to IEC/EN 60898-1 Ics 7,5 kA
Rated insulation voltage Ui V 440
Rated frequency f Hz 50/60
Characteristic B, C, D
Direction of incoming supply as required
lifespan
Electrical Operations ? 4000
Mechanical Operations ? 10000
Mechanical
Standard front dimension mm 45
Enclosure height mm 80
Mounting width per pole mm 17.5
Mounting Quick attachment with 3 latch positions for top-hat rail IEC/EN 60715
Degree of Protection IP20
Terminals top and bottom Twin-purpose ter...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XSDMV-240808-BF-2-PI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.