

INDUSTRIAL COMPONENT DATA

DILM225A-XKU-S 139561 Y7-139561 EATON ELECTRIC XTCEXTLA225A Cable terminal block, for DILM185A/225A

Brand: EATON - MOELLER | Manufacturer Part Number: DILM225A-XKU-S



Manufacturer	EATON - MOELLER
MPN / Reference	DILM225A-XKU-S
Catalog number	Y7-139561
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-DEF0D08779
Generated	2026-08-05

Product Overview

XTCEXTLA225A Cable terminal block, for DILM185A/225A

DILM225A-XKU-S

Eaton Moeller® series DILM Cable terminal block, for DILM185A/225A

Cable terminal block for contactor DILM185A/225A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors more than 170 A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM cable terminal block Catalog Number 139561 Model Code DILM225A-XKU-S
EAN 4015081363391 Product Length/Depth 117 mm Product Height 44 mm Product Width 116 mm Product Weight 0.484
kg Certifications IEC/EN 60947-4-1

CE

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

UL Category Control No.: NLDX

CSA File No.: 2389068

CSA

CSA Class No.: 3211-04

UL File No.: E29096

UL Catalog Notes Consisting of 3 box terminals Global

Accessory/spare part type Connection terminal Connection Connection options: round conductors, flexible and stranded, ribbon cables. Fitted with: Control cable connection Product category Accessories General

Ambient operating temperature - min -40 °C Ambient operating temperature - max 60 °C Fitted with: Control cable connection Product category Accessories Climatic environmental conditions

Terminal capacity 1 x (16 - 185) mm², solid, Main cables

2 x (16 - 150) mm², solid, Main cables

1 x (16 - 150) mm², flexible with ferrule, Main cables

2 x (16 - 120) mm², flexible with ferrule, Main cables

1 x (3 x 9 x 0.8) mm (Number of segments x width x thickness), Flat conductor, Main cable

2 x (10 x 16 x 0.8) mm (Number of segments x width x thickness), Flat conductor, Main cable

1 x (6 AWG-350 MCM)

2 x (6 AWG-350 MCM)

14 Nm, Screw terminals, Main cables

1 x (0.75 - 4) mm², solid, Control circuit cables

2 x (0.75 - 4) mm², solid, Control circuit cables

1 x (0.75 - 2.5) mm², flexible with ferrule, Control circuit cables

2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM225A-XKU-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.