

INDUSTRIAL COMPONENT DATA

XTMF/PI/NZM3/800/350-DF 192832 Y7-192832 EATON

ELECTRIC Circuit-breaker, 350 A, 3-pole, with electronic rele..

Brand: EATON - MOELLER | Manufacturer Part Number: XTMF/PI/NZM3/800/350-DF



Manufacturer	EATON - MOELLER
MPN / Reference	XTMF/PI/NZM3/800/350-DF
Catalog number	Y7-192832
Category	Component for installation (switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-02000E303C
Generated	2026-08-05

Product Overview

Circuit-breaker, 350 A, 3-pole, with electronic release for motor protection, withdrawable

XTMF/PI/NZM3/800/350-DF

XTMF/PI/NZM3/800/350-DF. LV switchgear

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Enclosures**

Additional Product Information

Circuit-breaker, 350 amp, 3-pole, with electronic release for motor protection, withdrawable Circuit-breaker NZM3, 3 pole,

Rated current = rated uninterrupted current $I_n = I_u$: 350, Installation type: Withdrawable, Screw connection,

Standard/Approval: IEC, Protective function: Motor protection [Delivery program

Product range Circuit-breaker Protective function Motor protection Standard/Approval IEC Installation type Withdrawable

Release system Electronic release Construction size NZM3 Description IEC/EN 60947-4-1, IEC/EN 60947-2

The circuit-breaker fulfills all requirements for AC-3 switching category.

R. m. s. value measurement and "thermal memory"

Adjustable time delay setting to overcome current peaks t_r at $6 \times I_r$ also infinity (without overload releases)

All AC-3 rating data applies to direct switching by the circuit-breaker under normal operating conditions. If, for example, a

contactor takes over the AC-3 switching under normal operating conditions, the full rated uninterrupted current applies to

the circuit-breaker, $I_n = I_u$. Number of poles 3 pole Standard equipment Screw connection Switching capacity 400 / 415v V

50 Hz $[I_{cu}]$ 70 kA Rated current = rated uninterrupted current $[I_n = I_u]$ Three hundred fifty Setting range Overload trip $[I_r]$ 175 -

350 Short-circuit releases $[I_{rm}]$ Non-delayed $[I_i = I_{nx} \dots]$ 2 - 14, Technical data

General Standards IEC/EN 60947 Protection against direct contact Finger and back of hand proof to VDE 0106 Part 100
Climatic proofing Damp heat, constan...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XTMF/PI/NZM3/800/350-DF with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.