

INDUSTRIAL COMPONENT DATA

PKE-XTUCP-65 168798 Y7-168798 EATON ELECTRIC XTPEXT065DD Trip block, 3p, 30-65A, system protection, standard

Brand: EATON - MOELLER | Manufacturer Part Number: PKE-XTUCP-65



Manufacturer	EATON - MOELLER
MPN / Reference	PKE-XTUCP-65
Catalog number	Y7-168798
Category	Tripping bloc for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-93007EBC99
Generated	2026-08-05

Product Overview

XTPEXT065DD Trip block, 3p, 30-65A, system protection, standard

PKE-XTUCP-65

Eaton Moeller® series PKE Trip block, 30 - 65 A, System protection, Connection to SmartWire-DT: no, For use with: PKE65 basic device

Electronic control unit for system protection as per IEC 60947-2, mounting without tools with PKE65 basic device, adjustable electronic wide-range overload protection (2, 1: 1), adjustable short-circuit releases

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKE Trip block Catalog Number 168798 Model Code PKE-XTUCP-65 EAN 4015081652891 Product Length/Depth 84.4 mm Product Height 69.9 mm Product Width 55 mm Product Weight 0.238 kg Certifications IEC/EN 60947

VDE 0660 Catalog Notes This is a product for Environment A (Industrial). In environment B (household) this device may cause undesirable radio interference. In this case the user may be obliged to take appropriate measures. Features &

Functions

Functions Line and cable protection

System protection

Overcurrent protection

Short-circuit protection Number of poles Three-pole General

Current flow times - min 1000 (Class 20) AC-4 cycle operation, Main conducting paths

500 (Class 5) AC-4 cycle operation, Main conducting paths

700 (Class 10) AC-4 cycle operation, Main conducting paths

900 (Class 15) AC-4 cycle operation, Main conducting paths

Note: Going below the minimum current flow time can cause overheating of the load (motor).

For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods. Cut-out periods - min ≤ 500 ms, main conducting paths, AC-4 cycle operation Degree of protection Device: IP20

Terminals: IP00 Operating frequency 60 Operations/h Overload release current setting - min 30 A Overload release current setting - max 65 A Overvoltage category III Pollution degree 3 Product category Accessories Protection Finger and back-of-hand proof, Protection a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKE-XTUCP-65 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.